



CoverShield Linear Fluorescent



Halco Linear Fluorescent CoverShield lamps have a skin-tight coating that restricts glass shards, mercury and phosphors within the lamp's envelope in the event of rupture. Halco CoverShield lamps are coated with co-polymer DuPont Nucrel, which is guaranteed to not become brittle or yellow. Halco T5 CoverShield lamps are coated with the highest rated PFA, allowing it to withstand heat up-to 600°F.

All Halco Covershield linear lamps meet NSF, CFIA, USDA, FDA and OSHA regulations.

Specifications:

- Skin-tight coating that eliminates air space between lamp and protective covering
- Coating doesn't crack, yellow or flake
- Less than 1% lumen loss
- T8 lamps block 99.7% of UV wavelengths under 400nm
- Rated for open or enclosed fixtures
- Safety coating is warranted for the rated life of the lamp
- Available in many sizes, wattages and color temperatures

- » Shatter-Resistant Lighting
- » Meets NSF, CFIA, USDA, FDA and OSHA regulations

Markets:

- Commercial
- Industrial

Applications:

- High bay fixtures
- Strip lighting
- Clean rooms
- Medical
- Food Service

where there's light, there's halco®

Contact your account representative at 800.677.3334 for pricing, orders and technical support.

Visit us at halcolighting.com

Ordering Information

Watt	Base	Product Number	Product Code	Description	Pkg. Qty.	Color Temp.	CRI	Initial Lumens	Mean Lumens	Avg. Life	MOL
T5											
28 Watt	Min. Bi-Pin	90016	F28T5/841/ECO/IC/CS	841 Phosphor	25	4100	86	2900	2750	24000	46"
54 Watt	Min. Bi-Pin	90051	F54T5/835/HO/ECO/IC/CS	835 Phosphor	25	3500	86	5000	4850	24000	46"
54 Watt	Min. Bi-Pin	90052	F54T5/841/HO/ECO/IC/CS	841 Phosphor	25	4100	86	5000	4850	24000	46"
54 Watt	Min. Bi-Pin	90053	F54T5/850/HO/ECO/IC/CS	850 Phosphor	25	5000	86	5000	4850	24000	46"
T8											
28 Watt	Med. Bi-Pin	90081	F28T8/835/ECO/IC/CS	835 Phosphor	25	3500	86	2800	2660	24000	48"
32 Watt	Med. Bi-Pin	90086	F32T8/735/ECO/IC/CS	735 Phosphor	25	3500	78	2850	2700	24000	48"
32 Watt	Med. Bi-Pin	90084	F32T8/735/ECO/CS	735 Phosphor	25	3500	78	2850	2700	24000	48"
32 Watt	Med. Bi-Pin	90087	F32T8/741/ECO/IC/CS	741 Phosphor	25	4100	78	2850	2700	24000	48"
32 Watt	Med. Bi-Pin	90085	F32T8/741/ECO/CS	741 Phosphor	25	4100	78	2850	2700	24000	48"
32 Watt	Med. Bi-Pin	90088	F32T8/750/ECO/IC/CS	750 Phosphor	25	5000	78	2850	2700	24000	48"
32 Watt	Med. Bi-Pin	90089	F32T8/750/ECO/CS	750 Phosphor	25	5000	78	2850	2700	24000	48"
32 Watt	Med. Bi-Pin	90091	F32T8/835/ECO/IC/CS	835 Phosphor	25	3500	86	3050	2900	24000	48"
32 Watt	Med. Bi-Pin	90094	F32T8/835/ECO/CS	835 Phosphor	25	3500	86	3050	2900	24000	48"
32 Watt	Med. Bi-Pin	90092	F32T8/841/ECO/IC/CS	841 Phosphor	25	4100	86	3050	2900	24000	48"
32 Watt	Med. Bi-Pin	90095	F32T8/841/ECO/CS	841 Phosphor	25	4100	86	3050	2900	24000	48"
32 Watt	Med. Bi-Pin	90093	F32T8/850/ECO/IC/CS	850 Phosphor	25	5000	86	3050	2900	24000	48"
32 Watt	Med. Bi-Pin	90096	F32T8/850/ECO/CS	850 Phosphor	25	5000	86	3050	2900	24000	48"



Atlanta | Carlstadt | Cleveland | Los Angeles | Houston | Phoenix