

Exit & Emergency

Indoor/Outdoor Remote Series

- White or Black Housing
- LED Adjustable Indoor/Outdoor Remotes
- Single or Double Head Configurations
- Round or Square Style
- Compatible with Select Evade Product Series
- All Models Include Mounting Plate
- LED Life Cycle Exceeding 10 Years



Specifications

Description

Halco's Exit/Emergency LED Remotes are high performance, high-impact, adjustable, lamp heads enclosed in a thermoplastic housing designed to optimize center-to-center spacing along the path of egress.

Construction & Mounting

- White or black housing
- Rugged, injection-molded, flame-retardant, high temperature thermoplastic housing
- Suitable for ceiling or wall mount
- Mounting canopy and hardware included
- For use with standard 4" j-box
- Suitable for indoor or outdoor applications

Certifications

- UL924
- NFPA 101 and NFPA 70
- CEC Title 20 compliant
- Wet or Damp location listed (model dependent)

Indoor/Outdoor Remote Series

Ordering Information

Remote Heads		
95010	EV-RH-1-IND	Evade Single Remote Indoor Round Head, White
97116	EMG-RH-1-IND-BK	Emergence Single Remote Indoor Round Head, Black
95011	EV-RH-2-IND	Evade Double Remote Indoor Round Head, White
97117	EMG-RH-2-IND-BK	Emergence Double Remote Indoor Round Head, Black
97012	EV2-RH-1-OUT-RD	Evade Single Remote Outdoor Round Head, White
97118	EMG-RH-1-OUT-BK	Emergence Single Remote Outdoor Round Head, Black
97013	EV2-RH-2-OUT-RD	Evade Double Remote Outdoor Round Head, White
97119	EMG-RH-2-OUT-BK	Emergence Double Remote Outdoor Round Head, Black
95015	EV-RHE-1-IND	Evade Single Remote Indoor Square Head, White
95016	EV-RHE-2-IND	Evade Double Remote Indoor Square Head, White

Remote Head Specifications

Product SKU	Product Code	Input Voltage	Input Wattage	Lumens	Operating Temperature
95010	EV-RH-1-IND	3.6VDC	.8W	85	0°C-50°C
97116	EMG-RH-1-IND-BK	3.6VDC	.8W	85	0°C-50°C
95011	EV-RH-2-IND	3.6VDC	1.5W	170	0°C-50°C
97117	EMG-RH-2-IND-BK	3.6VDC	1.5W	170	0°C-50°C
97012	EV2-RH-1-OUT-RD	3-12VDC	.8W	75	-25°C-50°C
97118	EMG-RH-1-OUT-BK	3-12VDC	.8W	75	-25°C-50°C
97013	EV2-RH-2-OUT-RD	3-12VDC	1.5W	150	-25°C-50°C
97119	EMG-RH-2-OUT-BK	3-12VDC	1.5W	150	-25°C-50°C
95015	EV-RHE-1-IND	4.8VDC	.8W	53	0°C-50°C
95016	EV-RHE-2-IND	4.8VDC	1.4W	96	0°C-50°C

Indoor/Outdoor Remote Series

Remote Head

EV-RH-1-IND EMG-RH-1-IND-BK



- Single, white or black, remote indoor head
- Suitable for damp location. UL cUL listed
- Compatible Halco Exits, EM Units and Combos with remote capacity

EV-RH-2-IND EMG-RH-2-IND-BK



- Double, white or black, remote indoor head
- Suitable for damp location. UL, cUL listed
- Compatible Halco Exits, EM Units and Combos with remote capacity

EV2-RH-1-OUT-RD EMG-RH-1-OUT-BK



- Single, white or black, remote outdoor head
- Suitable for wet location. UL, cUL listed
- Compatible Halco Exits, EM Units and Combos with remote capacity

EV2-RH-2-OUT-RD EMG-RH-2-OUT-BK



- Double, white or black, remote outdoor heads
- Suitable for wet location. UL, cUL listed
- Compatible Halco Exits, EM Units and Combos with remote capacity

EV-RHE-1-IND



- Single white remote indoor head
- Suitable for damp location. UL, cUL listed
- Compatible w/EV-EXE series

EV-RHE-2-IND



- Double white remote indoor head
- Suitable for damp location. UL, cUL listed
- Compatible w/EV-EXE series

Dimensions

