



LED A19 JA8 COMPLIANT LAMP

DIMMABLE GU24-BASE

SUGGESTED APPLICATIONS

- Residential
- Decorative, task lighting, fan lights

FEATURES

- 85% energy savings compared to 60W incandescent
- Advanced optics and thermal construction
- Dimmable down to 10% of total light output*
- RoHS compliant and mercury free



INPUT VOLTAGE: 120V

FREQUENCY: 60Hz

DIMMABLE: 100% TO 10%

EFFICACY: UP TO 80 LPW

CRI: 90

BEAM ANGLE: 220°

**LIFETIME (L70):
UP TO 25,000 HOURS**

**MINIMUM START
TEMPERATURE: -20°C**



**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.



LED A19 JA8 COMPLIANT LAMP

DIMMABLE GU24-BASE

ITEM SPECIFICATIONS | ORDER INFO

MODEL #	ORDER CODE	UPC	LUMENS	WATTAGE	INPUT CURRENT	CCT	BEAM ANGLE
LA19/10/927/GU24D	70725	751338016477	800	10W	83mA	2700K	230°
LA19/10/930/GU24D	70726	751338016484	800	10W	83mA	3000K	230°
LA19/10/940/GU24D	70727	751338016880	800	10W	83mA	4000K	230°

ORDERING GUIDE

Example: **LA19/10/927/GU24D**


PRODUCT	WATTAGE	CRI	BASE
LA19 = LAMP A19	10W	927 = 90 CRI AND 2700K 930 = 90 CRI AND 3000K 940 = 90 CRI AND 4000K	GU24D

ENERGY SAVINGS *Based on 3 hours/day and \$0.11/kWh*

MODEL #	LED WATTAGE	INCANDESCENT REPLACEMENT WATTAGE	WATTS SAVED	YEARLY SAVINGS	5 YEAR SAVINGS
LA19/10/9xx/GU24D	10W	60W	50W	\$24	\$120

DIMENSIONS | WEIGHT

MODEL #	A (IN)	B (IN)	WEIGHT (LBS.)
LA19/10/9xx/GU24D	4.35	2.36	0.1



NOTES

Dimming- This product is designed to be compatible with most leading-edge type incandescent and LED style dimmers. (Dimming range 100% down to 10%). Product performance may vary depending on dimmer manufacturer and circuit loading.

Suitable for use in totally enclosed fixtures.

*Dimmable with standard LED rated dimmer such as Leviton DSL06, IPL06, or Lutron CL type dimmers

Specifications are subject to change without prior notice. Replacement wattage shown depends on application and fixture.



Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.