



LED EXIT SIGNS - NYC APPROVED

EDGE-LIT SURFACE MOUNT

SUGGESTED APPLICATIONS

- Office, industrial, retail and other public spaces
- New York City applications

FEATURES

- New York City approved
- Meets NFPA 70, NFPA 101, UL924, NEC/OSHA Standards
- Battery backup with accessible test button for 90 minutes of illumination during a power outage
- Clear, single face or mirrored, double face configurations available
- Configurable arrows
- Ceiling, wall, or side mounting capability



INPUT VOLTAGE, FREQUENCY
HZ: 120/277V, 60HZ

EMERGENCY BACKUP: YES

EMERGENCY DURATION /
RUN TIME: 90 MINUTES

RECHARGE TIME : 24 HOURS

RECYCLE TIMES: 500 CYCLES

MOUNTING HEIGHT:
7.5 FT TO 15 FT

LOCATION RATING: DAMP

AMBIENT OPERATING
TEMPERATURE : 50°F TO 104°F

BATTERY TYPE: 4.8V NI-CAD1



BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™

Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.



LED EXIT SIGNS - NYC APPROVED

EDGE-LIT SURFACE MOUNT



ITEM SPECIFICATIONS | ORDER INFO

MODEL #	ORDER CODE	UPC	INPUT VOLTAGE	WATTAGE	LUMINANCE (AVG)	LETTER COLOR	PANEL TYPE	NUMBER OF FACES
ESEL/SFS/RCL/B-NYC	71096	751338035720	120/277V	3W	Avg. 41 cd/m2	Red	Clear	Single Face
ESEL/DFS/RMR/B-NYC	71098	751338035744	120/277V	3W	Avg. 36 cd/m2	Red	Mirrored	Double Face

ORDERING GUIDE

EXAMPLE: ESEL-SFS-RCL-B-NYC

PRODUCT	NUMBER OF FACES	LETTER COLOR	PANEL TYPE	EM TYPE	APPLICATION
ESEL = Exit Sign Edge-Lit	SF = Single face DF = Double face S = Surface Mount	R = Red	CL = Clear MR = Mirrored	B = Battery Backup	NYC = NYC Approved

DIMENSIONS | WEIGHT

MODEL #	A (IN)	B (IN)	C (IN)	WEIGHT (LBS.)	PALLET QTY
ESEL/RXS/RXX/B-NYC	14.6	11.6	1.6	3.24	96

NOTES

On all Exit and Emergency fixtures the battery will be prorated for 5 years.
Specifications subject to change without prior notice.
This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

WARNING: Some products included in this specification sheet may be subject to the warning requirements of California's Proposition 65. Please refer to your product packaging for more information.

