



LED Exit Signs

EDGE-LIT SURFACE MOUNT

Easy to Install Safety Solutions

Topaz's LED Edge-Lit Exit Signs are the ideal safety solution for office, industrial, retail and public places. Always ensure exits are clearly marked, even in the event of a power failure with the built-in 90-minute battery backup. These modern units have a clean look, with clear or mirrored panel and your choice of red or green EXIT letters. Surface mount installation is easy with the included canopy and mounting accessories.

FEATURES

- Meets NFPA 70, NFPA 101, UL924, NEC/OSHA Standards
- Battery backup with accessible test button for 90 minutes of illumination during a power outage
- Clear, single face or mirrored, double face configurations available
- Configurable arrows
- Ceiling, wall, or side mounting capability
- Recessed mount kit sold separately

SUGGESTED APPLICATIONS

- Office, industrial, retail and other public spaces



**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.

GENERAL SPECIFICATIONS

Input Voltage, Frequency Hz: 120/277V, 60Hz
Emergency Backup: Yes
Emergency Duration / Run Time: 90 minutes
Recharge Time: 24 hours
Recycle Times: 500 cycles
Mounting Height: 7.5 ft to 15 ft
Location Rating: Damp
Ambient Operating Temperature: 50°F to 104°F
Battery Type: 4.8V Ni-Cad¹

LED Exit Signs EDGE-LIT SURFACE MOUNT



**Battery Backup Push
to Test Button and
AC Supply Indicator**

**Mounting Accessories
Included**



Configurable Arrows



**Sleek Extruded Brushed
Aluminum Housing**

**6" Letter Height
3/4" Stroke**

ITEM SPECIFICATIONS / ORDER INFO

Catalog Number	Order Code	UPC	Lumens / Illuminance	Watts	Input Amps 120/277V	Letter Color	Panel Type	Number of Faces
ESEL/SFS/RCL/B	71095	751338035706	Average 55 cd/m2	3W	31/14mA	Red	Clear	Single Face
ESEL/DFS/RMR/B	71097	751338035737	Average 55 cd/m2	3W	31/14mA	Red	Mirrored	Double Face
ESEL/SFS/GCL/B	71099	751338035751	Average 78 cd/m2	3W	33/15mA	Green	Clear	Single Face
ESEL/DFS/GMR/B	71100	751338035850	Average 75 cd/m2	3W	33/15mA	Green	Mirrored	Double Face

NOMENCLATURE

Example: ESEL/SFS/RCL/B


ESEL = Exit Sign Edge-Lit / **SF** = Single Face **S** = Surface Mount / **R** = Red **CL** = Clear / **B** = Battery Backup
DF = Double Face **G** = Green **MR** = Mirrored

ACCESSORIES (SOLD SEPARATELY)

Catalog Number	Order Code	UPC	Description
ESEL/RMKIT	71103	751338035874	Recessed Mount Kit

PRODUCT DIMENSIONS / LINE DRAWING

Catalog Number	(A)	(B)	(C)	Weight
ESEL/XFS/XXX/B	12.1"	9.7"	1.6"	2.53 Lbs.



NOTES:

¹ On all exit and emergency fixtures the battery will be prorated for 5 years.

Specifications subject to change without prior notice.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

WARNING: Some products included in this specification sheet may be subject to the warning requirements of California's Proposition 65. Please refer to your product packaging for more information.

**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
 Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.