



LED Lamps

PERFORMANCE SERIES GLOBE

Highest Quality of Light

Topaz's Performance Series LED Globe lamps combine our latest LED-energy saving technology with our highest color rendering of >90 CRI. A high quality, long lasting alternative to traditional incandescent globes, these powerful lamps are ENERGY STAR® Certified and meet the requirements of California's Title 20 regulations. Ideal for use in bathrooms, vanities, and other decorative applications.

FEATURES

- 90 CRI provides exceptional color rendering
- Compliant with California Title 20, Tier 2 requirements
- 3000K model supports California Title 24, Part 6 requirements for high efficacy LED light source
- Dimmable down to 5% of total light output
- Approximately 90% energy savings over incandescent lamps
- ENERGY STAR Certified

APPLICATIONS

- Bathroom vanity lighting, decorative and task lighting
- Residential, hospitality, and retail



**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.

OVERVIEW

Input Voltage, Frequency: 120V, 60Hz

Power Factor/THD %: >0.9/<20%

CRI: >90

Average Rated Life (L70): 25,000 Hours

Location Rating: Damp Location

Ambient Operating Temperature: -4°F to 113°F

Lens Type: Shatter-resistant plastic

ORDER INFO

Catalog Number	Order Code	UPC	Watts	CCT (Kelvin)	PK-QTY	MOL (A)	MOD (B)	Weight
LG25/4/930/D-46	73394	751338033900	4W	3000K	1/6/24	4.3"	3.2"	.16 lbs
LG25/4/940/D-46	73395	751338033917	4W	4000K	1/6/24	4.3"	3.2"	.16 lbs

DIMENSIONS



SPECIFICATIONS

Catalog Number	Input Amps	Lumens	Lumens Per Watt	CBCP (cd)	Beam Angle	Base	Replacement Watts	Dimmable ¹	Enclosed Fixture Rating ²	ENERGY STAR [®]
LG25/4/930/D-46	50mA	360	90	-	170°	E26	40W	Y	Suitable	Y
LG25/4/940/D-46	50mA	360	90	-	170°	E26	40W	Y	Suitable	Y

ENERGY SAVINGS

	LED Watts	Incandescent Watts	Energy Saving, Watts	Yearly Savings	5 Year Savings
Based on 6 hours/day and .11¢/kwhr	4W	40W	36W	\$8.67	\$43.35

NOMENCLATURE

Example: LG25/4/927/D-46

LG25

LED Lamp
G25 Shape

4

Wattage

9XX

90 CRI and:

2700K CCT (Soft White)
3000K CCT (Warm White)
4000K CCT (Cool White)
5000K CCT (Daylight)

D

Dimmable

NOTES:

¹Dimming - This lamp is designed to be compatible with most leading-edge or incandescent style rotary or slide type dimmers. (Dimming range 100% - 5%) Performance may vary depending on dimmer.

²Suitable for enclosed fixtures, provided the ambient temperature inside the fixture does not exceed 113°F

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This product comes with a 5 year free replacement warranty from the date of purchase.

**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.