



LED T8 U-Bend Ballast Bypass

U6 FROSTED PLASTIC CONSTRUCTION

Features

- Ballast bypass version
- Extremely long life and energy efficient
- Full light around bend
- Polycarbonate construction
- No mercury

Specs

- 15.5W
- 120-277V
- 80 CRI
- 160° beam angle
- THD: <20%
- Power Factor: >0.9
- 50,000 Average Rated Life
- -20°C/-4°F Minimum Start Temperature

Applications

- Commercial offices, retail, schools and hospitality



Catalog Number	Order Code	UPC	Color Temp	Lumens	Wattage	Case Qty
L4T8B/U6/835/15F-70	74155	751338016354	3500K	1,950	15.5W	1/12
L4T8B/U6/840/15F-70	74156	751338016361	4000K	2,000	15.5W	1/12
L4T8B/U6/850/15F-70	74157	751338016378	5000K	2,000	15.5W	1/12

Specifications are subject to change without prior notice.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™

Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.