



LED LINEAR T8- BALLAST BYPASS

SINGLE & DOUBLE END - HIGH EFFICIENCY

SUGGESTED APPLICATIONS

- Commercial, hospitality
- Office
- Education
- Retail
- Warehouse

FEATURES

- Superior performance with up 162 PW
- Eliminate the ballast with direct wiring to line voltage
- Single & Double End wiring connection
- Frosted glass tube construction with PET coating
- Replacement for traditional fluorescent T8 tubes
- NSF Listed: NSF/ ANSI Standard 2 - Food Equipment, Splash Zone (Not for Direct Food Zone)
- Available in 4' length, 3500K 4000K, 5000K & 6500K CCT



INPUT VOLTAGE: 120-277V

FREQUENCY: 50/60HZ

POWER FACTOR, THD %:
>0.9; <25%

UL TYPE B, BALLAST BYPASS

LAMP EFFICACY:
UP TO 162 LPW

CRI: 80

BEAM ANGLE: 170°


LIGHT EMITTING AREA: 330°

LIFETIME (L70): 50,000 HOURS

ENCLOSED FIXTURE RATED

NON SHUNTED LAMP HOLDER
REQUIRED

BASE: G13



BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™

Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.



LED LINEAR T8- BALLAST BYPASS

SINGLE & DOUBLE END - HIGH EFFICIENCY

ITEM SPECIFICATIONS | ORDER INFO

MODEL #	ORDER CODE	UPC	LAMP LUMENS	WATTAGE	INPUT CURRENT @120V/277V	CCT	DLC ID
L4T8B-10-35K-GPSDE	75778	032886305252	1,700	10.5W	159/90mA	3500K	S-NI8UF4
L4T8B-10-40K-GPSDE	75779	032886305269	1,700	10.5W	159/90mA	4000K	S-7A98DY
L4T8B-10-50K-GPSDE	75780	032886305276	1,700	10.5W	159/90mA	5000K	S-CBA9QX
L4T8B-10-65K-GPSDE	75781	032886305283	1,700	10.5W	159/90mA	6500K	S-VIJP1F

NOMENCLATURE

Example: **L4T8B-15-xxK-PCEM**

PRODUCT	SIZE	SHAPE	UL TYPE	WATTAGE	CCT	OPTIONS
L = LINEAR TUBE	4FT	T8	BALLAST BYPASS	10.5W	3500K 4000K 5000K 6500K	G = GLASS CONSTRUCTION P = PET COATED SDE = SINGLE & DOUBLE END CONNECTION

ENERGY SAVINGS *Based on 12 hours/day and \$0.11/kWh*

MODEL #	LED LAMP WATTAGE	FLUORESCENT REPLACEMENT WATTAGE	WATTS SAVED	YEARLY SAVINGS	5 YEAR SAVINGS
L4T8B-10-xxK-GPSDE	10.5W	32W T8	22W	\$11	\$53

DIMENSIONS | WEIGHT

MODEL #	MOL (IN)	MOD (IN)	WEIGHT (LBS)
L4T8B-10-xxK-GPSDE	47.7	1.02	0.47



NOTES

DLC Primary Use - Internal Driver/Line Voltage (UL Type B) Lamps.
Bypass Type B operation requires non-shunted lamp holders. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. FIVE (5) YEAR LIMITED WARRANTY.

Specifications are subject to change without prior notice. Replacement wattage shown depends on application and fixture.

