



LED LINEAR T8- BALLAST BYPASS

SINGLE & DOUBLE END-CCT SELECTABLE

SUGGESTED APPLICATIONS

- Commercial, hospitality
- Office
- Education
- Retail
- Warehouse

FEATURES

- Choose from 5 color temperatures at installation with CCT selectable switch
- Eliminate the ballast with direct wiring to line voltage
- Single & Double End wiring connection
- Frosted glass tube construction with PET coating
- Replacement for traditional fluorescent T8 tubes
- NSF Listed: NSF/ ANSI Standard 2 - Food Equipment, Splash Zone (Not for Direct Food Zone)
- Available in 2', 3', 4' lengths



INPUT VOLTAGE: 120-277V

FREQUENCY: 50/60HZ

POWER FACTOR, THD %:
>0.9;<25%

UL TYPE B, BALLAST BYPASS

LAMP EFFICACY:
UP TO 129 LPW

CRI: 80

BEAM ANGLE: 170°


LIGHT EMITTING AREA 330°

LIFETIME (L70): 50,000 HOURS

ENCLOSED FIXTURE RATED

NON SHUNTED LAMP HOLDER
REQUIRED

BASE: G13



BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™

Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.



LED LINEAR T8- BALLAST BYPASS

SINGLE & DOUBLE END-CCT SELECTABLE

ITEM SPECIFICATIONS | ORDER INFO

MODEL #	ORDER CODE	UPC	SIZE	LAMP LUMENS	WATTAGE	INPUT CURRENT @120V/277V	CCT	DLC ID
L2T8B-9-CS-GPSDE	75782	032886305290	2FT	1,150	9W	148/77mA	3000K 3500K 4000K 5000K 6500K	S-JNFG2S
L3T8B-12-CS-GPSDE	75783	032886305306	3FT	1,450	12W	186/102mA	3000K 3500K 4000K 5000K 6500K	S-N3KCRY
L4T8B-14-CS-GPSDE	75784	032886305313	4FT	1,800	14W	188/122mA	3000K 3500K 4000K 5000K 6500K	S-IWMD56
L4T8B-17-CS-GPSDE	75785	032886305320	4FT	2,200	17W	219/146mA	3000K 3500K 4000K 5000K 6500K	S-A3G6Y0

NOMENCLATURE

Example: **L2T8B-9-CS-GPSDE**

PRODUCT	SIZE	SHAPE	UL TYPE	WATTAGE	CCT	OPTIONS
L = LINEAR TUBE	2FT 3FT 4FT	T8	BALLAST BYPASS	9W 12W 14W 17W	CS = COLOR SELECTABLE	G = GLASS CONSTRUCTION P = PET COATED SDE = SINGLE & DOUBLE END CONNECTION

ENERGY SAVINGS *Based on 12 hours/day and \$0.11/kWh*

MODEL #	LED LAMP WATTAGE	FLUORESCENT REPLACEMENT WATTAGE	WATTS SAVED	YEARLY SAVINGS	5 YEAR SAVINGS
L2T8B-9-CS-GPSDE	9W	17W T8	8W	\$4	\$19
L3T8B-12-CS-GPSDE	12W	25W T8	13W	\$6	\$31
L4T8B-14-CS-GPSDE	14W	32W T8	18W	\$9	\$43
L4T8B-17-CS-GPSDE	17W	32W T8	15W	\$7	\$36

DIMENSIONS | WEIGHT

MODEL #	MOL (IN)	MOD (IN)	WEIGHT (LBS)
L2T8B-9-CS-GPSDE	23.5	1.02	0.25
L3T8B-12-CS-GPSDE	35.7	1.02	0.38
L4T8B-14/17-CS-GPSDE	47.7	1.02	0.45



NOTES

DLC Primary Use - Internal Driver/Line Voltage (UL Type B) Lamps.
Bypass Type B operation requires non-shunted lamp holders. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.FIVE (5) YEAR LIMITED WARRANTY:

Specifications are subject to change without prior notice. Replacement wattage shown depends on application and fixture.



Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.