



LED 3-WAY A19 OMNIDIRECTIONAL

SUGGESTED APPLICATIONS

- Fan lights, decorative, recessed, task lighting
- Residential, hospitality, retail, restaurants, commercial

FEATURES

- 3 light levels (For use with 3-way light switch)
- 85% energy savings compared to 100W incandescent
- Suitable for use in totally enclosed luminaires
- Long life – up to 10X longer than traditional incandescents
- RoHS compliant and mercury free
- Plastic lens material provides shatter protection



INPUT VOLTAGE: 120V

FREQUENCY: 50/60Hz

THD%: <15%


**EQUIVALENT WATTAGE:
30/70/100W**

CRI: 80

BASE: E26

BEAM ANGLE: 300°

**LIFETIME (L70):
UP TO 25,000 HOURS**



**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.



LED 3-WAY A19

OMNIDIRECTIONAL

ITEM SPECIFICATIONS | ORDER INFO

MODEL #	ORDER CODE	UPC	LUMENS PER WATT	INITIAL LUMENS	WATTAGE	CCT
LA19/12/27K/3W-46	78983	751338019027	93/105/100	280/950/1200	3/9/12W	2700K
LA19/12/30K/3W-46	78984	751338019034	93/105/100	280/950/1200	3/9/12W	3000K

ORDERING GUIDE

Example: **LA19/12/27K/3W-46**


PRODUCT	WATTAGE	CRI	OPTIONS
LA19 = LED LAMP A19	12W = 12 WATTS	27K = 2700K 30K = 3000K	3W = 3-WAY

ENERGY SAVINGS Based on 3 hours/day and \$0.11/kWh

MODEL #	LED WATTAGE	INCANDESCENT REPLACEMENT WATTAGE	WATTS SAVED	YEARLY SAVINGS	5 YEAR SAVINGS
LA19/12/xxK/3W-46	12W	100W	88W	\$17.67	\$88.35

DIMENSIONS | WEIGHT

MODEL #	A (IN)	B (IN)	WEIGHT (LBS.)
LA19/12/xxK/3W-46	4.7	2.4	.16



NOTES

Suitable for enclosed fixtures. This device is not intended for use with emergency exits.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Specifications subject to change without notice.



Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
 Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change without notice.