



6" LED Recessed Can
New Construction IC Air Tight
RH6/NLED/IC/AT

Product Specifications

Features Quick Connect for use with LED Trim Module

Plaster Frame

Galvanized steel construction. The housing can be removed from plaster frame to provide access to the junction box

Installation

Bar Hanger


Pre-installed nails easily install in regular or engineered lumber. Bar hangers are adjustable from 13-5/8" to 25" and can be repositioned 90 degree on plaster frame

Junction Box



Listed for through branch circuit wiring. Contains seven 7/8" knockouts and four Romex pryouts with strain relief

Labels and Listings

cULus Listed for Feed Through Wiring
Certified under ASTM - E283 for Air Tight Construction



Product Code: 79992
Item # RH6/NLED/IC/AT



Specifications Subject To Change Without Notice

Series	Aperture Size	Lamp Orientation	Construction	Lamp Style	Insulation Contact	Airtight	Voltage	Options
RH= Recessed Housing	4	Blank=Vert	R=Remodel	Blank=Incand.	Blank=Non-IC	Blank=Non-AT	Blank=120	Any Modifications
	5	H=Hor	N=New	C=CFL	IC=IC	AT=AT	H=120/277	
	6			G=GU				
				LED=LED				
				LV=Low Voltage				

