



4" LED CYLINDER WALL MOUNT UP/DOWNLIGHT BLACK CYLINDER WITH PHOTOCELL

SUGGESTED APPLICATIONS

- Hospitality (Hotel)
- Restaurants and coffee shops
- Convenience stores
- Retail spaces
- Residential
- Multi-family
- Airports

FEATURES

- Control center for 5CCT and light distribution (up/down/full light options)
- Control center for Photocell on/off and power (12W/16W/20W)
- Black die-cast aluminum housing with UV resistant tempered glass lens
- Wall mounting
- For indoor and outdoor use
- Additional black knockout included if photocell is not needed



INPUT VOLTAGE, FREQUENCY:
120-277V AND 50/60Hz

DIMMING: DOWN TO 0%, 0-10V

CRI: >90

LIFETIME (L70):
UP TO 54,000 HOURS

BEAM ANGLE: 40°

IK (IMPACT RATING): IK04

POWER FACTOR: >0.9, <20%

**SURGE PROTECTION
RATING:** 4kV

MOUNTING OPTIONS:
WALL MOUNTING

POWER LEADS LENGTH:
5.9" LEAD LENGTH



CONTROL CENTER FOR LIGHT
DISTRIBUTION AND CCT


CONTROL CENTER FOR PHOTOCELL
ON/OFF AND POWER



**POWER
SELECT**



**IP65
WATERPROOF**



**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612
Fax 800.880.0822 | halcolighting.com | Atlanta | Cleveland | Houston | Phoenix | New Jersey © 2026 Halco Lighting
Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies.
All sizes and specifications are subject to change without notice.



4" LED CYLINDER WALL MOUNT UP/DOWNLIGHT BLACK CYLINDER WITH PHOTOCELL

ITEM SPECIFICATIONS | ORDER INFO

MODEL #	UPC	INPUT VOLTAGE MAX. INPUT CURRENT	POWER SELECTABLE WATTAGE	LUMENS @ 2700K	LUMENS @ 3000K	LUMENS @ 3500K	LUMENS @ 4000K	LUMENS @ 5000K	LPW @ 4000K
CLW-20PCS-BK	032886793561	120-277V 185mA@20W AC120V	12W	1,020	1,080	1,140	1,140	1,140	95
			16W	1,360	1,440	1,520	1,520	1,520	95
			20W	1,700	1,800	1,900	1,900	1,900	95

DEFAULT SETTING: 20W / 4000K / PHOTOCELL OFF

ORDERING GUIDE

Example: CLW-20PCS-BK

PRODUCT	POWER SELECTABLE	CCT SELECTABLE	FINISH COLOR
CLW = CYLINDER LIGHT WALL MOUNT	20P=12W/16W/20W	CS=2700K/3000K/3500K/4000K/5000K	BK = BLACK FINISH

DIMENSIONS | WEIGHT

MODEL #	A (IN)	B (IN)	C (IN)	WEIGHT (LBS.)	Pallet Quantity (pcs)* 48"x 40"x 60"
CLW-20PCS-BK	4.00	7.00	11.00	4.33	90

