

## Exit & Emergency

### Evade Exit Series

- Compact, Led Thermoplastic Exit Sign
- Choice Of Red or Green Stencil Face
- Remote Capacity Option
- Multiple Mounting Options
- Universal Single / Double Face
- Led Life-Cycle Exceeding 10 Years

### Specifications

#### Description

The Evade Exit Sign Series offers a code compliant exit sign solution for hallway, stairwell, and other Life Safety applications. The low profile design makes it ideal to mount on ceilings or walls in surface or end mount configurations, indicating the path of egress for a minimum of 90 minutes after a power loss. Available with remote capacity.

#### Electrical

- 120 / 277 VAC, 60Hz input
- Emergency test button and battery charging indicator
- Long-life maintenance free NiCad battery
- 24 hour recharge time
- 10°C - 40°C operating temperature

#### Certifications

- UL924 Damp Location listed
- NFPA 101 and NFPA 70
- CEC T20 Compliant



#### Construction & Mounting

- Rugged, injection-molded, flame retardant, high-temperature, white thermoplastic housing
- Fully illuminated 6" characters with 3/4" stroke
- Field-selectable, snap in and out chevrons
- Suitable for wall, ceiling and end mount
- Universal J-Box mounting pattern on back plate

# Evade Exit Series

## Ordering Information

Product SKU	Product Code	Product Description
95000	EV-EXE-GR	Evade Exit Sign with Green Lettering
95001	EV-EXE-RD	Evade Exit Sign with Red Lettering
95002	EV-EXE-GR-RC	Evade Exit Sign with Green Lettering and Remote Capacity
95003	EV-EXE-RD-RC	Evade Exit Sign with Red Lettering and Remote Capacity
Remote Heads		
95015	EV-RHE-1-IND	Evade Single Indoor Square Remote Head
95016	EV-RHE-2-IND	Evade Double Indoor Square Remote Head
96012	EV-RH-1-OUT	Evade Single Outdoor Round Remote Head
95013	EV-RH-2-OUT	Evade Double Outdoor Round Remote Head

## Specifications Table

	EV-EXE-GR	EV-EXE-RD	EV-EXE-GR-RC	EV-EXE-RD-RC
Letter Color	Green	Red	Green	Red
Input	.30mA Max		.40mA Max	
Wattage	2.3W		2.7W	
Battery	Ni-cad 2.4V300mAh		N-cad HT 4.8V1000mAh	
Recharge Time	24 Hours			
Input Voltage	120 or 277 VAC			
Output Voltage	4.8V DC			
Frequency	60Hz			
Housing	Injection-Molded Thermoplastic Housing			
Testing Function	Manual Push to Test Button			
Operating Temperature	10°C to 40°C			
Listings & Compliance	UL 924, CEC Title 20, NFPA 70 & NFPA 101			
Environment	Damp Location Listed			
Warranty*	2 Year			

\*All life safety equipment, including emergency lighting for path of egress must be maintained, serviced, and tested in accordance with all National Fire Protection Association (NFPA) and local codes. Failure to perform the required maintenance, service, or testing could jeopardize the safety of occupants and will void all warranties.

Exit & Emergency

## Evade Exit Series

### Remote Head Specifications

Product SKU	Product Code	Input Voltage	Input Wattage	Lumens
95015	EV-RHE-1-IND	4.8VDC	.8W	53
95016	EV-RHE-2-IND	4.8VDC	1.4W	96
96012	EV-RH-1-OUT	3.6-24VDC	.8W	90
95013	EV-RH-2-OUT	3-12VDC	1.5W	180

### Remote Head

#### EV-RHE-1-IND

- Single, White, Indoor Remote Head
- Suitable for Damp Location. UL, cUL Listed



#### EV-RHE-2-IND

- Double, White, Indoor Remote Head
- Suitable for Damp Location. UL, cUL Listed



#### EV-RH-1-OUT

- Single, Gray, Outdoor Remote Head
- Suitable for Wet Location. UL, cUL Listed



#### EV-RH-2-OUT

- Double, White, Outdoor Remote Head
- Suitable for Wet Location. UL, cUL Listed



### Dimensions

