

CBT-LED-24A-45-8XX-P

2' × 4' LED CENTER BASKET FIXTURE



45W, 120–277V Input, 0–10V Dimming

APPLICATION

Used for commercial recessed ceiling applications



5 YEAR
WARRANTY



PRODUCT FEATURES

- Architectural grade center basket volumetric design
- Powered by Keystone 0–10V dimming LED drivers
- Smooth diffused lens for even appearance
- 0–10V dimming, 10% minimum
- Compatible with Keystone SmartSafe emergency backups
- Compatible with Keystone occupancy sensors
- Ambient operating temperature: –20°C/–4°F to 50°C/122°F
- UL Listed 1598: Suitable for dry and damp locations
- THD: <20%
- PF: >0.95
- LED chip lifetime: L70 >100,000 hrs @ 25°C/77°F ambient fixture temp.
- Low optical flicker

PRODUCT SPECIFICATIONS

Catalog Number	Color Temperature	Nominal Length	Input Voltage	Wattage	CRI	Lumen Output	Efficacy
CBT-LED-24A-45-835-P	3500K	2 ft. × 4 ft.	120–277V	45W	>82.0	5,535 L	124 lm/W
CBT-LED-24A-45-840-P	4000K	2 ft. × 4 ft.	120–277V	45W	>82.0	5,670 L	126 lm/W
CBT-LED-24A-45-850-P	5000K	2 ft. × 4 ft.	120–277V	45W	>82.0	5,760 L	128 lm/W

PHYSICAL SPECIFICATIONS

