



### KT-LED15T8-U1G-840-D

T8 LED LAMP

### **DESCRIPTION**

15W T8 U-Bend LED | 4000K | > 80 CRI | High Efficiency

LAMP TYPE: U-Bend **BULB TYPE: T8 LED** 

BASE TYPE: G13 (Medium Bi-Pin)

**WATTAGE: 15W** 

**COLOR TEMPERATURE: 4000K** 

**COLOR RENDERING INDEX (CRI):** >80

**WARRANTY:** 5 Years













### **PRODUCT FEATURES**

- Replacement for conventional fluorescent lamp
- UL Classified
- 50,000+ hour lifetime
- Approximately 40% more energy efficient than standard U-Bend fluorescent lamps
- Environmentally friendly: No mercury used

- Integral driver (isolated) eliminates the need for an external ballast or driver
- Instant startup
- Frosted lens eliminates pixelation
- Operating temperature: -20°C/-4°F to 45°C/113°F
- Bare lamp efficacy: 110+ lumens per watt
- Suitable for dry and damp locations

### **OPERATING SPECIFICATIONS**


### FIFCTRICAL AND PERFORMANCE CHARACTERISTICS

LEGITIONE AND I ENGINEERIC SHARACTERIOTIOS										
Input Voltage	CRI	Bare Lamp Wattage	Nominal Lamp Lumens	Beam Angle	Nominal Bare Lamp Efficacy	Power Factor	Max. THD			
120-277Vac	>80	15W	1,780	220°	118 lm/W	>0.9	25%			


### **RATED LIFE**

**L70 (Hours)** 50,000





### POLAR CANDELA DISTRIBUTION



Maximum Candela = 1248.55 Located at Horizontal Angle = 0, Vertical Angle = 0

- 1 Violet Vertical Plane through Horizontal Angles (90–270)
- 2 Green Vertical Plane through Horizontal Angles (0–180)






# KT-LED15T8-U1G-840-D

### **WIRING**

Re-wire fixture as shown below.



### PHYSICAL CHARACTERISTICS



### LAMP DIMENSIONS

A (Illuminated Length)	20.30"
B (Body Length)	22.44"
C (Diameter)	1.09"
D (Width)	1.62"

NOMINAL LENGTH: 22.44"

BASE TYPE: G13 (Medium Bi-Pin)

### **ORDERING INFORMATION**

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS	
KT-LED15T8-U1G-840-D-CP	Carton Pack (Egg Crate Packaging)	25	Quick Ship	

### **CATALOG NUMBER BREAKDOWN**

## KT-LED15T8-U1G-840-D-CP

- 1 Keystone Technologies
- 2 LED Lamp
- 3 Wattage
- 4 Lamp Type
- 5 Nominal Size
- 6 Glass
- **7** 800 Series
- 8 Color Temperature
- 9 Direct-Drive Series
- 10 Packaging Style