

Features & Benefits

- No rewiring needed
- Works with fluorescent electronic T5 ballast
- Long life
- High CRI
- Instant on, no delay
- Convenient and quick installation
- Utilizes existing T5 sockets
- No Mercury, No UV
- Compatible with controls and sensors
- Works in cold temperature applications
- Full Glass Design
- Super Wide View Angle, 240
- 5 Year Warranty



* EMERGENCY BALLAST RESTRICTIONS




RetroFlex™
LED T5 LAMP • Simplicity.
Commercial Grade LED T5 Lamp

Specification Data

Order Code	Length	Lamp Wattage	System Wattage	CCT	Initial Lumens	CRI	Beam Angle	Lamp Efficacy	System Efficacy	Life	DLC
L48T5HO/830/24G-EB	48 in	24W	27W	3000K	3100	83	240	129	115	50000	No
L48T5HO/835/24G-EB	48 in	24W	27W	3500K	3100	83	240	129	115	50000	No
L48T5HO/840/24G-EB	48 in	24W	27W	4000K	3200	83	240	133	118	50000	No
L48T5HO/850/24G-EB	48 in	24W	27W	5000K	3200	83	240	133	118	50000	No

Wiring Diagram



DLC Information

Order Code	DLC Product ID	DLC Product Model	DLC Version
L48T5HO/830/24G-EB	PLWIPVXQGYNW	L48T5HO/830/24G-EB(-aa)	5.1
L48T5HO/835/24G-EB	PLYVSXVM5FPY	L48T5HO/835/24G-EB(-aa)	5.1
L48T5HO/840/24G-EB	PLTCO057BNCL	L48T5HO/840/24G-EB(-aa)	5.1
L48T5HO/850/24G-EB	PLSIQWFR23O1	L48T5HO/850/24G-EB(-aa)	5.1

* Please refer to "Ballast Compatibility List" for compatible battery backup and/or emergency ballasts.

* Please refer to "Ballast Compatibility List" on Related Downloads.

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.