

	Produ	ıct Spec	
Category	Up/Down LED Wall Sconce		
Item Code	7022		
Stock Code	LED-FXDWS10/830/NI	PICTURE	
Mounting	Wall Mount		
Housing Color	Nickel		

Electric Characteristics		Photometric Ch	Photometric Characteristics		
Rated Wattage (W)	10	Lumen (lm)	700		
Tested Wattage (W)	10	Efficacy (lm/w)	70		
Input Voltage (V)	100~277	CRI	80		
Voltage Frequency (Hz)	50/60	сст (к)	3000		
nput Current (A)	0.1	Beam Angle (∘)	38		
Power Factor	>0.9	General Characteristics			
Replacement Wattage (W)	90	Operating Temperature	-4°F~104°F		
Surge protect level		Storage Temperature	-4°F~122°F		
Dimmable	No	IP rating	UL Wet Location		
THD	<20%	Rated Life	50000 hrs		
		Warranty	5 years		
Produc	et Dimensions	Suggested A	Accessory		
Weight (lbs.)					
Height (in)	6.75				
Length (in)	5				
Length (in) Width (in)	5 3.13				
Width (in)					
Width (in) Mounting Height (ft)					
Width (in) Mounting Height (ft)					
Width (in) Mounting Height (ft) Cable Length (ft)	3.13	alifications			
Width (in) Mounting Height (ft) Cable Length (ft)	3.13	alifications LM79	V		
Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	3.13 Qua		V V		
Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC	3.13 Qua	LM79			
Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC CEC	3.13 Qua	LM79 LM80	٧		
Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC CEC	3.13 Qua	LM79 LM80 IES File	٧		
Width (in) Mounting Height (ft)	3.13 Qua	LM79 LM80 IES File FDA	٧		