## SATCO NUVO

Project Name

Location

Prepared By



## **SATCO 67-116**

REC EL EXIT SIGN - SF GR CLR

## Notes

[www] 01-15-2024 02:40

| General                   |           |
|---------------------------|-----------|
| Status                    | Active    |
| Fixture Type              | Exit Sign |
| Finish                    | Clear     |
| Wattage                   | 2.94W     |
| Indoor or Outdoor Fixture | Indoor    |

| Specifications        |                             |
|-----------------------|-----------------------------|
| Technology            | LED                         |
| Voltage               | 120V/277V                   |
| Operating Temperature | +10C (+50F) to +40C (+104F) |
| Dimmable              | Non-Dimmable                |
| Lens Material         | Acrylic                     |
| Weight (lb.)          | 5.2                         |
| Material              | Aluminum                    |

| Dimensions   |       |
|--------------|-------|
| Height (in.) | 11    |
| Width (in.)  | 15.75 |
| Length (in.) | 4     |

| Compliance             |                               |
|------------------------|-------------------------------|
| Safety Listing         | ULus - Certified              |
| Location Rating        | Damp                          |
| Energy Star            | No                            |
| CA T20 / T24 Rationale | T20 Listed                    |
| California Status      | Lawful for sale in California |
| Title 20 / 24 Status   | Lawful for sale               |
| California Prop 65     | Lead                          |
| RoHS Compliant         | Yes                           |
| FCC Compliant          | Yes                           |

| Additional Information |  |
|------------------------|--|
| Additional Information | Input Wattage: 2.94W; Output<br>Wattage: 0.4W; Energy Used in<br>Maintenance Mode: 2.94W   |
| Specification Note     | Aluminum, Acrylic Panel, 4.8V AA300mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Lumens/Illuminance: 73cd/m2 average; Letter Height: 6 in.; Letter Stroke: 0.75 in. |
| Includes               | Mounting hardware and accessories  |
| Warranty               | 2 Year Limited   |

