## SATCO NUVO

Project Name

Location

Prepared By



## **SATCO S11278**

5.5MR16/GU10/RGB/TW/T20/SF

## Notes

www] 03-13-2023 01:50

CA T20 / T24 Rationale

California Status

General	
Status	Active
Watts	5.5W
Incandescent Equivalent	50W
Volts	120V
Shape	MR16
Base	Bi Pin GU10
ANSI Base	GU10
Finish	Clear
CCT (Kelvin)	2700K-5000K
Temperature	Warm to Cool White/Color Changeable
CRI	90
Lumens	385L
Beam Spread	50
Dimmable	Yes-Dimmable
Hours Rated	25000
Lamp Type	MR
Technology	LED
Smart Product Info	
IOT Enabled	Yes
Voice Assistants Supported	Siri; Alexa; Hey Google; SmartThings
Electrical	
Operating Frequency	60Hz
Operating Frequency Specifications	60Hz
Specifications	
Specifications  Dimming Type	Smart-Starfish App only
Specifications  Dimming Type  Dimming Note	Smart-Starfish App only Only with Starfish App
Specifications  Dimming Type  Dimming Note  Power Factor	Smart-Starfish App only Only with Starfish App  0.7
Specifications  Dimming Type  Dimming Note  Power Factor  Operating Position	Smart-Starfish App only Only with Starfish App
Specifications  Dimming Type  Dimming Note  Power Factor  Operating Position  Operating Temperature	Smart-Starfish App only Only with Starfish App  0.7 Universal
Specifications  Dimming Type  Dimming Note  Power Factor  Operating Position  Operating Temperature  Physical	Smart-Starfish App only Only with Starfish App  0.7 Universal -20C (-4F) to +45C (+113F)
Specifications  Dimming Type  Dimming Note  Power Factor  Operating Position  Operating Temperature  Physical  MOL	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)
Specifications  Dimming Type Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20
Specifications  Dimming Type  Dimming Note  Power Factor  Operating Position  Operating Temperature  Physical  MOL  MOD  Housing Color	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20 White
Specifications  Dimming Type  Dimming Note  Power Factor  Operating Position  Operating Temperature  Physical  MOL  MOD  Housing Color  Lens Finish	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20 White Clear
Specifications  Dimming Type Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color  Lens Finish  Lens Material	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20 White Clear Plastic (PS)
Specifications  Dimming Type Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color Lens Finish Lens Material Weight (lb.)	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20 White Clear
Specifications  Dimming Type Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color  Lens Finish  Lens Material	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20 White Clear Plastic (PS)
Specifications  Dimming Type Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color Lens Finish Lens Material Weight (lb.)	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20 White Clear Plastic (PS)
Specifications  Dimming Type Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color Lens Finish Lens Material Weight (lb.)  Additional Information	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20 White Clear Plastic (PS) 0.08
Specifications  Dimming Type Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color  Lens Finish  Lens Material  Weight (lb.)  Additional Information  Rated For Enclosed Fixture	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20 White Clear Plastic (PS) 0.08
Specifications  Dimming Type Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color  Lens Finish  Lens Material  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20 White Clear Plastic (PS) 0.08
Specifications  Dimming Type Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color Lens Finish Lens Material Weight (lb.)  Additional Information  Rated For Enclosed Fixture Warranty  Compliance	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20 White Clear Plastic (PS) 0.08  Yes 3 Year Limited
Specifications  Dimming Type Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color  Lens Finish  Lens Material  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20 White Clear Plastic (PS) 0.08  Yes 3 Year Limited
Specifications  Dimming Type Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color  Lens Finish  Lens Material  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating	Smart-Starfish App only Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.20 White Clear Plastic (PS) 0.08  Yes 3 Year Limited  cULus Damp

T20 Listed

Lawful for sale in California

Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







