SATCO NUVO

Project Name

Location

Prepared By



SATCO S11392

4.5MR16/LED/40'/830/12V

Notes

www] 11-01-2023 00:12:5

General	
Status	Active
Watts	4.5W
Incandescent Equivalent	35W
Volts	12V
Shape	MR16
Base	Bi Pin GU5.3
ANSI Base	GU5.3
Finish	Gray
CCT (Kelvin)	3000K
Temperature	Soft White
CRI	80
Lumens	360L
Beam Spread	40
Dimmable	Yes-Dimmable
Dimming Note	Check the transformer/driver MFG for dimmer compatibility
Hours Rated	25000
Lamp Type	MR
Technology	LED
Electrical	
Operating Frequency	60Hz
CBCP	730
Candlepower	730
Power Factor	0.94
i uwei i aciui	0.34
Operating Temperature	-25C (-13F) to +45C (+113F)
Operating Temperature	
Operating Temperature Physical	-25C (-13F) to +45C (+113F)
Operating Temperature Physical MOL	-25C (-13F) to +45C (+113F)
Operating Temperature Physical MOL MOD	-25C (-13F) to +45C (+113F) 1.77 1.97
Operating Temperature Physical MOL MOD Lensed	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp
Operating Temperature Physical MOL MOD Lensed Lens Finish	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color Weight (lb.)	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray 0.08
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray 0.08
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray 0.08
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray 0.08 Yes 5 Year Limited - 10 hr per day
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray 0.08 Yes 5 Year Limited - 10 hr per day
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray 0.08 Yes 5 Year Limited - 10 hr per day cULus Damp
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray 0.08 Yes 5 Year Limited - 10 hr per day CULus Damp No
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star CA T20 / T24 Rationale	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray 0.08 Yes 5 Year Limited - 10 hr per day cULus Damp No T20 Listed
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star CA T20 / T24 Rationale California Status	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray 0.08 Yes 5 Year Limited - 10 hr per day cULus Damp No T20 Listed Lawful for sale in California
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star CA T20 / T24 Rationale California Status Title 20 / 24 Status	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray 0.08 Yes 5 Year Limited - 10 hr per day CULus Damp No T20 Listed Lawful for sale in California Lawful for sale
Operating Temperature Physical MOL MOD Lensed Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star CA T20 / T24 Rationale California Status Title 20 / 24 Status RoHS Compliant	-25C (-13F) to +45C (+113F) 1.77 1.97 Lensed Lamp Array Plastic Gray 0.08 Yes 5 Year Limited - 10 hr per day CULus Damp No T20 Listed Lawful for sale in California Lawful for sale Yes

All Rights Reserved

http://www.satco.com/

