## SATCO NUVO

Project Name

Location Prepared By



Notes

www] 11-01-2023 00:12:5

General	
Status	Active
Watts	12W
Incandescent Equivalent	75W
Volts	120V
Shape	A19
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	90
Lumens	1050L
Beam Spread	230
Dimmable	Non-Dimmable
Hours Rated	15000
Photocell or Sensor	Has PIR Sensor
Lamp Type	Туре А
Technology	LED
Electrical	
Operating Frequency	60Hz
Power Factor	0.7
Operating Temperature	-20C (-4F) to +40C (+104F)
Physical	
MOL	5.11
MOD	2.36
Weight (lb.)	0.27
Additional Information	
Additional information	
	The lamp has an integrated motion-activated sensor designed to activate between dusk and dawn. It remains inactive in the
Additional Info	absence of motion but turns on for a duration of 5 minutes once motion is detected. This functionality can be overridden by toggling the bulb's switch on and off twice within a span of 3 seconds, allowing it to remain continuously illuminated like a standard light bulb.
Additional Info  Rated For Enclosed Fixture	a duration of 5 minutes once motion is detected. This functionality can be overridden by toggling the bulb's switch on and off twice within a span of 3 seconds, allowing it to remain continuously illuminated like a
	a duration of 5 minutes once motion is detected. This functionality can be overridden by toggling the bulb's switch on and off twice within a span of 3 seconds, allowing it to remain continuously illuminated like a standard light bulb.
Rated For Enclosed Fixture	a duration of 5 minutes once motion is detected. This functionality can be overridden by toggling the bulb's switch on and off twice within a span of 3 seconds, allowing it to remain continuously illuminated like a standard light bulb.  No  To achieve optimal sensor reading, make sure the sensor is facing the desired motion area within proper
Rated For Enclosed Fixture  Installation Notes	a duration of 5 minutes once motion is detected. This functionality can be overridden by toggling the bulb's switch on and off twice within a span of 3 seconds, allowing it to remain continuously illuminated like a standard light bulb.  No  To achieve optimal sensor reading, make sure the sensor is facing the desired motion area within proper distance and angle.  Dual Mode Capable: Motion or On-
Rated For Enclosed Fixture  Installation Notes  Specification Note	a duration of 5 minutes once motion is detected. This functionality can be overridden by toggling the bulb's switch on and off twice within a span of 3 seconds, allowing it to remain continuously illuminated like a standard light bulb.  No  To achieve optimal sensor reading, make sure the sensor is facing the desired motion area within proper distance and angle.  Dual Mode Capable: Motion or On-Off Switch
Rated For Enclosed Fixture  Installation Notes  Specification Note  Warranty	a duration of 5 minutes once motion is detected. This functionality can be overridden by toggling the bulb's switch on and off twice within a span of 3 seconds, allowing it to remain continuously illuminated like a standard light bulb.  No  To achieve optimal sensor reading, make sure the sensor is facing the desired motion area within proper distance and angle.  Dual Mode Capable: Motion or On-Off Switch
Rated For Enclosed Fixture  Installation Notes  Specification Note  Warranty  Compliance	a duration of 5 minutes once motion is detected. This functionality can be overridden by toggling the bulb's switch on and off twice within a span of 3 seconds, allowing it to remain continuously illuminated like a standard light bulb.  No  To achieve optimal sensor reading, make sure the sensor is facing the desired motion area within proper distance and angle.  Dual Mode Capable: Motion or On-Off Switch  3 Year Limited
Rated For Enclosed Fixture  Installation Notes  Specification Note  Warranty  Compliance  Safety Listing	a duration of 5 minutes once motion is detected. This functionality can be overridden by toggling the bulb's switch on and off twice within a span of 3 seconds, allowing it to remain continuously illuminated like a standard light bulb.  No  To achieve optimal sensor reading, make sure the sensor is facing the desired motion area within proper distance and angle.  Dual Mode Capable: Motion or On-Off Switch  3 Year Limited
Rated For Enclosed Fixture  Installation Notes  Specification Note  Warranty  Compliance  Safety Listing  Location Rating	a duration of 5 minutes once motion is detected. This functionality can be overridden by toggling the bulb's switch on and off twice within a span of 3 seconds, allowing it to remain continuously illuminated like a standard light bulb.  No  To achieve optimal sensor reading, make sure the sensor is facing the desired motion area within proper distance and angle.  Dual Mode Capable: Motion or On-Off Switch  3 Year Limited  CULus  Wet

California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







