

Project Name

Location Prepared By



## **SATCO S11754**

30T8/LED/72-CCT/BP/R17D

Notes

3 44 04 0000 00 40 5

Status	Active
Watts	30W
ncandescent Equivalent	125W
Fluorescent Equivalent	87W
/olts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Recessed Double Contact HO/VHO
ANSI Base	R17d
lominal Length	72
inish	White
CCT (Kelvin)	4000K/5000K/6500K
emperature	Cool White to Daylight
RI	83
umens	4200L/4300L/4100L
Beam Spread	180
Dimmable	Non-Dimmable
lours Rated	50000
amp Type	Linear
echnology	LED
Electrical	
Sallasting Requirements	Ballast Bypass
perating Frequency	50/60Hz

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	<25%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	70
MOD	1
Material	Glass / Plastic
Lens Finish	Frost
Lens Material	Glass
Housing Color	White

Additional Information	
Shatter-Proof Type	PET Coated
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Compliance		
Safety Listing	cRUus - Recognized Component; ETLus - Listed; cULus - Classified	
Location Rating	Damp	
Energy Star	No	
DLC Approved	No	
CA T20 / T24 Rationale	Exempt - Base Not Regulated	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
RoHS Compliant	Yes	

FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="http://www.satco.com/">http://www.satco.com/</a>







