

Project Name

Location

Prepared By



SATCO S11760

10T8/LED/24-CCT/DM/BP-DR

Notes

[www] 02-27-2023 01:59:16

General

Status	Active
Watts	10W
Incandescent Equivalent	125W
Fluorescent Equivalent	25W/21W
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	24.00
Finish	White
CCT (Kelvin)	3500K/4000K/5000K
Temperature	Neutral White to Natural Light
CRI	83
Lumens	1425L/1450L/1450L
Beam Spread	180
Dimmable	Yes-Dimmable
Hours Rated	50000
Technology	LED

Electrical

Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	23.78
MOD	1.00
Material	Glass / Plastic
Lens Finish	Frosted
Lens Material	Glass
Housing Color	White

Additional Information

Shatter-Proof Type	PET Coated
Warranty	5 Year Limited - T8 LED Bulbs

Compliance

Safety Listing	cULus - Listed; cULus - Classified; cETLus - Listed
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	S-18R2WN
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes



