SATCO | NUVO

LED REFLECTOR LAMPS

DIM TO WARM | CCT SELECTABLE





DIM TO WARM FEATURE FROM 3000K DOWN TO 2000K

5-CCT SELECTABLE

90 CRI HIGH QUALITY LIGHT

R20, BR30, & BR40 MODELS

SUITABLE FOR USE IN ENCLOSED FIXTURES

SUGGESTED APPLICATIONS

Indoor Residential
Commercial
Accent & Track Lighting
Recessed Downlighting

Transform your lighting experience with SATCO|NUVO's LED reflector light bulbs. Designed for superior energy efficiency, these bulbs provide vibrant, true-to-life white light with an impressive CRI of 90. Available in R20, BR30, and BR40 shapes, these lamps fit seamlessly into a variety of fixtures to suit many different needs. Offering a 5 CCT range from a soft 2700K to a crisp 5000K, they also feature a dim-to-warm capability, allowing you to enjoy the nostalgic charm of traditional incandescent lighting with modern efficiency. This feature dims the light from 3000K to a cozy 2000K, creating a warm and inviting atmosphere. With a wide 120° beam angle, these bulbs are versatile enough to suit any environment, from living rooms and dining areas to offices, museums, and retail stores, ensuring the perfect ambiance for every setting.

DIM-TO-WARM | 90 CRI | DAMP LOCATION | ENCLOSED FIXTURE | TITLE 20 | TITLE 24 | 25,000 HOURS | 3 YEAR WARRANTY | TRUSTED WARRANTY

SATCO | NUVO

LED REFLECTOR LAMPS
DIM TO WARM | CCT SELECTABLE

GENERAL SPECIFICATIONS

Input Voltage: 120V
Frequency: 60Hz
Power Factor: 0.9
CCT Selectable: 2700K/3000K/3500K/4000K/5000K
CCT (D2W): 3000K to 2000K
Dimming: Phase-Cut Dimmable Down to 10%
CRI: 90
Beam Angle: 120°


Functional Life: 25,000 Hours
Location Rating: Damp
Ambient Operating Temperature: -20°C (-4°F) to +40°C (+104°F)
Rated for Enclosed Fixture: Yes
Housing Material / Color: Plastic/White
Lens Material: Polycarbonate
Base: E26
Warranty: 3 Year Limited

ITEM SPECIFICATIONS / ORDER INFO

Item	Shape	Lumens	Wattage	Replacement Wattage	THD%	Efficacy	Input Current
S11782	R20	525L	5.8W	50W	19.80%	90 LPW	0.07A
S11783	BR30	650L	7W	65W	18.70%	92 LPW	0.08A
S11784	BR30	850L	8.5W	65W	19.80%	100 LPW	0.09A
S11785	BR40	1080L	11W	80W	14.50%	98 LPW	0.12A

DIMENSIONS / WEIGHTS

Item	MOL (A)	MOD (B)	Weight
S11782	3.86"	2.48"	0.10 Lbs.
S11783	5.04"	3.74"	0.22 Lbs.
S11784	5.04"	3.74"	0.22 Lbs.
S11785	6.30"	5.00"	0.37 Lbs.



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Lamps may not be compatible with all dimmers.

Not compatible with all photo sensors, motion sensors, or timers.

This device is not intended for use with emergency exits.

Replacement wattage shown depends on application and fixture.

Specifications are subject to change without prior notice.

Visit satco.com/service/warranty for complete warranty details.

SATCO.COM | 800-437-2826

© Satco Products, Inc. All rights reserved. Rev. 6/24 SN1674