

Project Name

Location

Prepared By



**Notes**

[www] 01-15-2024 02:40:09

**General**

Status	Active
Recessed Can Size	6 in.
Wattage	15W
Voltage	120V
Finish	White
CCT (Kelvin)	2700K/3000K/3500K/4000K/5000K
Color Temperature	Warm to Cool White
Lumen Output	1280L-1400L
Indoor or Outdoor Fixture	Indoor

**Specifications**

Technology	LED
CRI	90
Beam Angle	40
Rated Hours	50000
Operating Temperature	-20C (-4F) to +45C (+113F)
Dimmable	Yes-Dimmable
Sloped Ceiling	Yes

**Dimensions**

Width (in.)	7.48
Height (in.)	2.17
Weight (lb.)	1.06

**Compliance**

Safety Listing	cETLus - Listed
Location Rating	Damp
Energy Star	Yes
ES Unique ID	ESID-2470768
DLC Approved	No
Air Tight Rated	Yes
IC Rated	Yes
CA T20 / T24 Rationale	California T24 2016 - 2022 JA8 Listed
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Listed
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

**Additional Information**

Installation Notes	*If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)
Warranty	5 Year Limited - LED Commercial Downlights

