

Project Name

Location

Prepared By



Notes

[www] 01-15-2024 02:40:09

General

| | |
|---------------------------|-------------------------------|
| Status | Active |
| Recessed Can Size | 6 in. |
| Wattage | 15W |
| Voltage | 120V |
| Finish | Black |
| CCT (Kelvin) | 2700K/3000K/3500K/4000K/5000K |
| Color Temperature | Warm to Cool White |
| Lumen Output | 1280L-1400L |
| Indoor or Outdoor Fixture | Indoor |

Specifications

| | |
|-----------------------|----------------------------|
| Technology | LED |
| CRI | 90 |
| Beam Angle | 40 |
| Rated Hours | 50000 |
| Operating Temperature | -20C (-4F) to +45C (+113F) |
| Dimmable | Yes-Dimmable |
| Sloped Ceiling | Yes |

Dimensions

| | |
|--------------|------|
| Width (in.) | 7.48 |
| Height (in.) | 2.17 |
| Weight (lb.) | 1.06 |

Compliance

| | |
|------------------------|---------------------------------------|
| Safety Listing | cETLus - Listed |
| Location Rating | Damp |
| Energy Star | Yes |
| ES Unique ID | ESID-2470768 |
| DLC Approved | No |
| Air Tight Rated | Yes |
| IC Rated | Yes |
| CA T20 / T24 Rationale | California T24 2016 - 2022 JA8 Listed |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | California T24 Listed |
| California Prop 65 | Lead |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |

Additional Information

| | |
|--------------------|--|
| Installation Notes | *If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973) |
| Warranty | 5 Year Limited - LED Commercial Downlights |

