



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S12355 - 6.5 Watt T6 LED; Clear Finish; DC Base; 5000K; 120 Volt**



**GENERAL**

Company	SATCO
EA Height	2.95
EA Width	1.5
EA Length	1.5
Candle Power	45.0
Center Beam Candle Power	45
Dimmable Text	120V only
Lamp Filament	LED
Material	Ceramic / Polycarbonate (PC)
Fixture Type	Tubular
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 1.5KV
Total Harmonic Distortion	70%
CCT Selectable	False
Wattage Selectable	False
Finish Family	Clear
Amps	0.056A
Has Camera	False
IOT Enabled	False
Lens Material	Polycarbonate (PC)
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	50W

**ELECTRICAL**

CCT (Kelvin Temp)	5000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	300
Color Temp	Natural Light
CRI	80+
Dimming Type	Forward Phase or Reverse Phase or Phase Selectable or Triac
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +40C (+104F)
Lumens	650L
Volts	120v
Watts	6.5W

**PHYSICAL**

Lamp Base	Bayonet Double Contact
Finish	Clear
Housing Color	White
ANSI Base	BA15d
Lamp Type	T6
MOD Lamps	0.75
MOL	2.83

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	True

**FEATURES**

Flicker Free	False
--------------	-------

**PACKAGING**

UPC	045923123559
Case Cube	1.1904
Case Height	13.62
Case Length	17.44
Case Quantity	200
Case UPC	10045923123556
Case Weight	17.04
Case Width	8.66
EA Cube	0.0038
EA Height	2.95
EA Length	1.5
EA Quantity	1
EA Weight	0.075
EA Width	1.5
Inner Cube	0.1004
Inner Height	6.42
Inner Length	8.07
Inner Quantity	20
Inner UPC	20045923123553
Inner Weight	1.62
Inner Width	3.35
Pack Type	Box
Web Length	2.83
Web Width	0.75

**COMPLIANCE**

CA Regulations	Exempt - Base Not Regulated
CA Status	Lawful for sale in California
FCC Compliant	True
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cETLus
CA Compliance Text	Lawful for sale
DLC Approved	False
Title 20	Exempt
T24 Compliant	False