SATCO NUVO

Project Name

Location Prepared By



N	ha	۰

www] 11-13-2023 02:12:2

General	
Status	Active
Watts	7W
Incandescent Equivalent	50W
Fluorescent Equivalent	25W
Volts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Recessed Double Contact HO/VHO
ANSI Base	R17d
Nominal Length	18
Finish	White
CCT (Kelvin)	4000K/5000K/6500K
Temperature	Cool White to Daylight
CRI	83
Lumens	950L/1000L/900L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
TUD	050/
THD	25%
Operating Temperature	-20C (-4F) to +45C (+113F)
_	
Operating Temperature	
Operating Temperature Physical	-20C (-4F) to +45C (+113F)
Operating Temperature Physical MOL	-20C (-4F) to +45C (+113F)
Operating Temperature Physical MOL MOD	-20C (-4F) to +45C (+113F) 15.81 1.13
Operating Temperature Physical MOL MOD Material	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC)
Operating Temperature Physical MOL MOD Material Lens Finish	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost Plastic
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Weight (lb.)	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost Plastic
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Weight (lb.) Additional Information	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost Plastic 0.26
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Weight (lb.) Additional Information Tube Guard Use	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost Plastic 0.26
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Weight (lb.) Additional Information Tube Guard Use Rated For Enclosed Fixture	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost Plastic 0.26 No Yes
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Weight (lb.) Additional Information Tube Guard Use Rated For Enclosed Fixture Warranty	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost Plastic 0.26 No Yes
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Weight (lb.) Additional Information Tube Guard Use Rated For Enclosed Fixture Warranty Compliance	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost Plastic 0.26 No Yes 5 Year Limited - T8 LED Bulbs cULus - Classified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Weight (lb.) Additional Information Tube Guard Use Rated For Enclosed Fixture Warranty Compliance Safety Listing	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost Plastic 0.26 No Yes 5 Year Limited - T8 LED Bulbs CULus - Classified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Weight (lb.) Additional Information Tube Guard Use Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost Plastic 0.26 No Yes 5 Year Limited - T8 LED Bulbs CULus - Classified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT Damp
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Weight (lb.) Additional Information Tube Guard Use Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost Plastic 0.26 No Yes 5 Year Limited - T8 LED Bulbs cULus - Classified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT Damp No
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Weight (lb.) Additional Information Tube Guard Use Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost Plastic 0.26 No Yes 5 Year Limited - T8 LED Bulbs CULus - Classified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT Damp No No
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Weight (lb.) Additional Information Tube Guard Use Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale	-20C (-4F) to +45C (+113F) 15.81 1.13 Polycarbonate (PC) Frost Plastic 0.26 No Yes 5 Year Limited - T8 LED Bulbs CULus - Classified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT Damp No No Exempt - Base Not Regulated

RoHS Compliant	Yes	
FCC Compliant	Yes	
NSF Approved	ETL Sanitation listed (conforms to NSF)	
SDS Sheet	LED Lamp	

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







