

Project Name

Location Prepared By



## **SATCO S21924**

14T8/LED/48-865/BP/SE-DE

## Notes

General	
Status	Active
Watts	14W
Incandescent Equivalent	75W
Fluorescent Equivalent	25W/28W/32W
Volts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss White
CCT (Kelvin)	6500K
Temperature	Daylight
CRI	82
Lumens	1800L
Beam Spread	210
Hours Rated	50000
Lamp Type	
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)
Dhysical	
Physical	
MOL	47.78
MOD	1.1
Material	Glass
Lens Finish	Gloss White
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.44
Additional Information	
Tube Guard Use	Approved for use with tube guards
Specification Note	Built-in shock resistant circuit - (not hot until both ends are installed)
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass
Compliance	
Safety Listing	cULus - Classified; cRUus - Recognized Component
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLCMB3ZLZZ39
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale

Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="http://www.satco.com/">http://www.satco.com/</a>







