SATCO' NUVO

Project Name

Location

Prepared By



SATCO S23115 130W/LED/HID-HB/5K/120-277V

Notes

[www] 11-20-2023 01:02:47

General	
	Active
Status	
Substitute Watts	<u>S33115</u> 130W
	250W
Incandescent Equivalent	400W
HID Equivalent Volts	120V-277V
-	HB77
Shape Base	
ANSI Base	Mogul Extended EX39
Finish	Translucent White
	5000K
CCT (Kelvin)	
CRI	Natural Light 80
Lumens	
Beam Spread	115 Vaa Diamabla
Dimmable	Yes-Dimmable
Hours Rated	35000
Lamp Type	Hi-Bay
Technology Min Compartment Size	LED Length: 16.5 in. Width: 16.5 in.
Ballasting Requirements	Height: 13 in. Ballast Bypass
Electrical	
Operating Frequency	50-60Hz
Candlepower	5000
	Oton Dimming
Dimming Type	Step Dimming
Dimming Type Dimming Note	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch
	Dimmable only via the built-in dimmer on the lamp. Not dimmable
Dimming Note	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch
Dimming Note Power Factor	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95
Dimming Note Power Factor Operating Position	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal
Dimming Note Power Factor Operating Position Surge Protection	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F)
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 12.4
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 12.4 9.65
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 12.4 9.65 Plastic
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 12.4 9.65 Plastic White
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.)	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 12.4 9.65 Plastic White
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 12.4 9.65 Plastic White 2.98
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 12.4 9.65 Plastic White 2.98 Yes Fixture has built-in dimming control
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Specification Note	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 12.4 9.65 Plastic White 2.98 Yes Fixture has built-in dimming control feature
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Specification Note Warranty	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 12.4 9.65 Plastic White 2.98 Yes Fixture has built-in dimming control feature
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Specification Note Warranty Compliance Safety Listing	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 12.4 9.65 Plastic White 2.98 Yes Fixture has built-in dimming control feature 3 Year Limited CULus - Classified; cULus -
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Specification Note Warranty Compliance	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 12.4 9.65 Plastic White 2.98 Yes Fixture has built-in dimming control feature 3 Year Limited CULus - Classified; cULus - Certified
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Specification Note Warranty Compliance Safety Listing Location Rating	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.99/0.95 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 12.4 9.65 Plastic White 2.98 Yes Fixture has built-in dimming control feature 3 Year Limited CULus - Classified; cULus - Certified Damp

CA T20 / T24 Rationale	T20 Exempt - Not A Regulated Product
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved For More Information Visit: <u>http://www.satco.com/</u>

