## SATCO NUVO

Project Name

Location

Prepared By



## **SATCO S23162**

36W/LED/CCT/277-480V/E26

## Notes

[www] 11-20-2023 01:02:4

Location Rating

DLC Approved

NSF Approved

CA T20 / T24 Rationale

Energy Star

General	
Status	Active
Watts	36W
Incandescent Equivalent	125W
HID Equivalent	175W
Volts	277V-480V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80
Lumens	4680L/5040L/4860L
Beam Spread	300
Dimmable	Yes-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 10.55 in. Width: 8.00 in. Height: 8.00 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	50/60Hz
Operating Frequency Dimming Type	50/60Hz Smart-Starfish App only
Dimming Type	Smart-Starfish App only
Dimming Type Dimming Note	Smart-Starfish App only Only Dimmable Via Sensor Port
Dimming Type Dimming Note Power Factor	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9
Dimming Type Dimming Note Power Factor Operating Position	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal
Dimming Type Dimming Note Power Factor Operating Position Surge Protection	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 7.73
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)  7.73 3.35
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)  7.73 3.35 Clear
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)  7.73 3.35 Clear Plastic
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)  7.73 3.35 Clear Plastic Dark Gray
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)  7.73 3.35 Clear Plastic
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.)	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)  7.73 3.35 Clear Plastic Dark Gray Optional
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.) Additional Information	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)  7.73 3.35 Clear Plastic Dark Gray Optional 1.4
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.)  Additional Information Rated For Enclosed Fixture	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)  7.73 3.35 Clear Plastic Dark Gray Optional 1.4  Yes
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.) Additional Information	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)  7.73 3.35 Clear Plastic Dark Gray Optional 1.4
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.)  Additional Information Rated For Enclosed Fixture	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)  7.73 3.35 Clear Plastic Dark Gray Optional 1.4  Yes
Dimming Type Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating	Smart-Starfish App only Only Dimmable Via Sensor Port 0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)  7.73 3.35 Clear Plastic Dark Gray Optional 1.4  Yes IP64

Damp

Exempt - >2600 Lumens

No No

No

California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







