

Project Name

Location Prepared By



Notes

General	
Status	Active
Watts	13W
Incandescent Equivalent	50W
Fluorescent Equivalent	28W
Volts	120V-277V
Ballast Type	Туре В
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	48
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	83
Lumens	1650L
Beam Spread	240
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
	D. II D
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor THD	0.9
	20%
Operating Temperature	-25C (-13F) to +45C (+113F)
Operating Temperature	
Operating Temperature  Physical	-25C (-13F) to +45C (+113F)
Operating Temperature  Physical  MOL	-25C (-13F) to +45C (+113F)
Operating Temperature  Physical  MOL  MOD	-25C (-13F) to +45C (+113F)  46 0.83
Operating Temperature  Physical  MOL  MOD  Material	-25C (-13F) to +45C (+113F)  46  0.83  Glass
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish	-25C (-13F) to +45C (+113F)  46  0.83  Glass  Frost
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material	-25C (-13F) to +45C (+113F)  46  0.83  Glass  Frost  Glass
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color	-25C (-13F) to +45C (+113F)  46  0.83  Glass  Frost  Glass  White
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information	-25C (-13F) to +45C (+113F)  46 0.83 Glass Frost Glass White 0.4
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Shatter-Proof Type	-25C (-13F) to +45C (+113F)  46  0.83  Glass  Frost  Glass  White  0.4  PET Coated
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Shatter-Proof Type  Rated For Enclosed Fixture	-25C (-13F) to +45C (+113F)  46 0.83 Glass Frost Glass White 0.4  PET Coated Yes
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Shatter-Proof Type	-25C (-13F) to +45C (+113F)  46  0.83  Glass  Frost  Glass  White  0.4  PET Coated
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Shatter-Proof Type  Rated For Enclosed Fixture  Warranty	-25C (-13F) to +45C (+113F)  46 0.83 Glass Frost Glass White 0.4  PET Coated Yes 5 Year Limited - T5 LED Bulbs -
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Shatter-Proof Type  Rated For Enclosed Fixture	-25C (-13F) to +45C (+113F)  46  0.83  Glass  Frost  Glass  White  0.4  PET Coated  Yes  5 Year Limited - T5 LED Bulbs - Ballast Bypass
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Shatter-Proof Type  Rated For Enclosed Fixture  Warranty	-25C (-13F) to +45C (+113F)  46 0.83 Glass Frost Glass White 0.4  PET Coated Yes 5 Year Limited - T5 LED Bulbs -
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Shatter-Proof Type  Rated For Enclosed Fixture  Warranty  Compliance	-25C (-13F) to +45C (+113F)  46  0.83  Glass  Frost  Glass  White  0.4  PET Coated  Yes  5 Year Limited - T5 LED Bulbs - Ballast Bypass  CULus - Classified; cULus - Certified; ETLus - SANITATION
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Shatter-Proof Type  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing	-25C (-13F) to +45C (+113F)  46 0.83 Glass Frost Glass White 0.4  PET Coated Yes 5 Year Limited - T5 LED Bulbs - Ballast Bypass  CULus - Classified; cULus - Certified; ETLus - SANITATION RECOGNIZED COMPONENT
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Shatter-Proof Type  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating	-25C (-13F) to +45C (+113F)  46  0.83  Glass  Frost  Glass  White  0.4  PET Coated  Yes  5 Year Limited - T5 LED Bulbs - Ballast Bypass  CULus - Classified; cULus - Certified; ETLus - SANITATION RECOGNIZED COMPONENT  Damp
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Shatter-Proof Type  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating  Energy Star	-25C (-13F) to +45C (+113F)  46  0.83  Glass  Frost  Glass  White  0.4  PET Coated  Yes  5 Year Limited - T5 LED Bulbs - Ballast Bypass  CULus - Classified; cULus - Certified; ETLus - SANITATION  RECOGNIZED COMPONENT  Damp  No
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Shatter-Proof Type  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating  Energy Star  DLC Approved	-25C (-13F) to +45C (+113F)  46  0.83  Glass  Frost  Glass  White  0.4  PET Coated  Yes  5 Year Limited - T5 LED Bulbs - Ballast Bypass  CULus - Classified; cULus - Certified; ETLus - SANITATION RECOGNIZED COMPONENT  Damp  No  Yes
Operating Temperature  Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Shatter-Proof Type  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating  Energy Star  DLC Approved  DLC ID	-25C (-13F) to +45C (+113F)  46  0.83  Glass  Frost  Glass  White  0.4  PET Coated  Yes  5 Year Limited - T5 LED Bulbs - Ballast Bypass  CULus - Classified; cULus - Certified; ETLus - SANITATION RECOGNIZED COMPONENT  Damp  No  Yes  PL3XLAY3AKAW

Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="http://www.satco.com/">http://www.satco.com/</a>







