

Project Name

Location Prepared By



Notes

ww] 11-20-2023 01:02:

General	
Status	Active
Watts	16W
Incandescent Equivalent	100W
Fluorescent Equivalent	39W
Volts	120V-277V
Ballast Type	Туре В
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	36
Finish	Frost
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	83
Lumens	1900L
Beam Spread	240
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-25C (-13F) to +45C (+113F)
Operating Temperature Physical	-25C (-13F) to +45C (+113F)
Operating Temperature Physical MOL	-25C (-13F) to +45C (+113F)
Operating Temperature Physical MOL MOD	-25C (-13F) to +45C (+113F) 34 0.83
Operating Temperature Physical MOL MOD Material	-25C (-13F) to +45C (+113F) 34 0.83 Glass
Operating Temperature Physical MOL MOD Material Lens Finish	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.)	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White 0.3
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Shatter-Proof Type	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White 0.3
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Shatter-Proof Type Rated For Enclosed Fixture	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White 0.3 PET Coated Yes 5 Year Limited - T5 LED Bulbs -
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Shatter-Proof Type Rated For Enclosed Fixture Warranty	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White 0.3 PET Coated Yes 5 Year Limited - T5 LED Bulbs -
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Shatter-Proof Type Rated For Enclosed Fixture Warranty Compliance	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White 0.3 PET Coated Yes 5 Year Limited - T5 LED Bulbs - Ballast Bypass CULus - Classified; cULus - Certified; ETLus - SANITATION
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Shatter-Proof Type Rated For Enclosed Fixture Warranty Compliance Safety Listing	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White 0.3 PET Coated Yes 5 Year Limited - T5 LED Bulbs - Ballast Bypass CULus - Classified; cULus - Certified; ETLus - SANITATION RECOGNIZED COMPONENT
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Shatter-Proof Type Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White 0.3 PET Coated Yes 5 Year Limited - T5 LED Bulbs - Ballast Bypass CULus - Classified; cULus - Certified; ETLus - SANITATION RECOGNIZED COMPONENT Damp
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Shatter-Proof Type Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White 0.3 PET Coated Yes 5 Year Limited - T5 LED Bulbs - Ballast Bypass CULus - Classified; cULus - Certified; ETLus - SANITATION RECOGNIZED COMPONENT Damp No
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Shatter-Proof Type Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White 0.3 PET Coated Yes 5 Year Limited - T5 LED Bulbs - Ballast Bypass CULus - Classified; cULus - Certified; ETLus - SANITATION RECOGNIZED COMPONENT Damp No No
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Shatter-Proof Type Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale	-25C (-13F) to +45C (+113F) 34 0.83 Glass Frost Glass White 0.3 PET Coated Yes 5 Year Limited - T5 LED Bulbs - Ballast Bypass CULus - Classified; cULus - Certified; ETLus - SANITATION RECOGNIZED COMPONENT Damp No No Exempt - Base Not Regulated

Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







