

Project Name

Location Prepared By



## **SATCO S39900**

9T8/LED/24-830/BP/SE-DE

Notes

General	
	Activo
Status Watts	Active 9W
	40W
Incandescent Equivalent	17W
Fluorescent Equivalent Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	24
Finish	Gloss White
CCT (Kelvin)	3000K
Temperature	Warm White
CRI	82
Lumens	1100L
Beam Spread	210
Hours Rated	50000
Lamp Type	T8
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)
Operating Temperature  Physical	-20C (-4F) to +45C (+113F)
	-20C (-4F) to +45C (+113F)
Physical	
Physical MOL	23.78
Physical MOL MOD	23.78
Physical MOL MOD Material	23.78 1.1 Glass
Physical  MOL  MOD  Material  Lens Finish	23.78  1.1  Glass Gloss White
Physical  MOL  MOD  Material  Lens Finish  Lens Material	23.78 1.1 Glass Gloss White Glass
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)	23.78 1.1 Glass Gloss White Glass White
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color	23.78 1.1 Glass Gloss White Glass White 0.24
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)	23.78 1.1 Glass Gloss White Glass White
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information	23.78  1.1  Glass  Gloss White  Glass  White  0.24  Equivalent CCT selectable option
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information	23.78 1.1 Glass Gloss White Glass White 0.24  Equivalent CCT selectable option available in S11764
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Use	23.78  1.1  Glass  Gloss White  Glass  White  0.24  Equivalent CCT selectable option available in S11764  Approved for use with tube guards  Built-in shock resistant circuit - (not
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Tube Guard Use  Specification Note	23.78  1.1  Glass  Gloss White  Glass  White  0.24  Equivalent CCT selectable option available in S11764  Approved for use with tube guards  Built-in shock resistant circuit - (not hot until both ends are installed)  5 Year Limited - T8 LED Bulbs -
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Use  Specification Note  Warranty	23.78  1.1  Glass  Gloss White  Glass  White  0.24  Equivalent CCT selectable option available in S11764  Approved for use with tube guards  Built-in shock resistant circuit - (not hot until both ends are installed)  5 Year Limited - T8 LED Bulbs - Ballast Bypass  cULus - Classified; cRUus -
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Tube Guard Use  Specification Note  Warranty  Compliance  Safety Listing	23.78  1.1  Glass  Gloss White  Glass  White  0.24  Equivalent CCT selectable option available in S11764  Approved for use with tube guards  Built-in shock resistant circuit - (not hot until both ends are installed)  5 Year Limited - T8 LED Bulbs - Ballast Bypass
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Tube Guard Use  Specification Note  Warranty  Compliance  Safety Listing  Location Rating	23.78  1.1  Glass  Gloss White  Glass  White  0.24  Equivalent CCT selectable option available in S11764  Approved for use with tube guards  Built-in shock resistant circuit - (not hot until both ends are installed)  5 Year Limited - T8 LED Bulbs - Ballast Bypass  cULus - Classified; cRUus - Recognized Component
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Tube Guard Use  Specification Note  Warranty  Compliance  Safety Listing  Location Rating  Energy Star	23.78  1.1  Glass  Gloss White  Glass  White  0.24  Equivalent CCT selectable option available in S11764  Approved for use with tube guards  Built-in shock resistant circuit - (not hot until both ends are installed)  5 Year Limited - T8 LED Bulbs - Ballast Bypass  cULus - Classified; cRUus - Recognized Component  Damp
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Tube Guard Use  Specification Note  Warranty  Compliance  Safety Listing  Location Rating  Energy Star  DLC Approved	23.78  1.1  Glass  Gloss White  Glass  White  0.24  Equivalent CCT selectable option available in S11764  Approved for use with tube guards  Built-in shock resistant circuit - (not hot until both ends are installed)  5 Year Limited - T8 LED Bulbs - Ballast Bypass  cULus - Classified; cRUus - Recognized Component  Damp  No  Yes
Physical  MOL  MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Tube Guard Use  Specification Note  Warranty  Compliance  Safety Listing  Location Rating  Energy Star	23.78  1.1  Glass  Gloss White  Glass  White  0.24  Equivalent CCT selectable option available in S11764  Approved for use with tube guards  Built-in shock resistant circuit - (not hot until both ends are installed)  5 Year Limited - T8 LED Bulbs - Ballast Bypass  cULus - Classified; cRUus - Recognized Component  Damp  No

California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







