

Project Name

Location Prepared By



SATCO S39901

9T8/LED/24-835/BP/SE-DE

Notes

Occupation	
General	
Status	Active
Watts	9W
Incandescent Equivalent	40W
Fluorescent Equivalent	17W
Volts	120V-277V
Ballast Type	Type B
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	24
Finish	Gloss White
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	82
Lumens	1100L
Beam Spread	210
Hours Rated	50000
Lamp Type	
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	
MOL	22.70
MOL	23.78
MOD	1.1
MOD Material	1.1 Glass
MOD Material Lens Finish	1.1 Glass Gloss White
MOD Material Lens Finish Lens Material	1.1 Glass Gloss White Glass
MOD Material Lens Finish Lens Material Housing Color	1.1 Glass Gloss White Glass White
MOD Material Lens Finish Lens Material Housing Color Weight (lb.)	1.1 Glass Gloss White Glass
MOD Material Lens Finish Lens Material Housing Color	1.1 Glass Gloss White Glass White
MOD Material Lens Finish Lens Material Housing Color Weight (lb.)	1.1 Glass Gloss White Glass White
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info	1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use	1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note	1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs -
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note Warranty	1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs -
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note Warranty Compliance	1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus - Classified; cRUus -
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note Warranty Compliance Safety Listing	1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus - Classified; cRUus - Recognized Component
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note Warranty Compliance Safety Listing Location Rating	1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus - Classified; cRUus - Recognized Component Damp
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note Warranty Compliance Safety Listing Location Rating Energy Star	1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus - Classified; cRUus - Recognized Component Damp No
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus - Classified; cRUus - Recognized Component Damp No Yes

California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







