

Project Name

Location Prepared By



9T8/LED/24-850/BP/SE-DE

Notes

General	
Status	Active
Watts	9W
Incandescent Equivalent	40W
	17W
Fluorescent Equivalent Volts	120V-277V
Ballast Type	Type B
Shape	. <u>Туре В</u>
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	24
Finish	Gloss White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	82
Lumens	1150L
Beam Spread	210
Hours Rated	50000
Lamp Type	T8
Technology	LED
recimology	
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)
Operating Temperature Physical	-20C (-4F) to +45C (+113F)
	-20C (-4F) to +45C (+113F)
Physical	
Physical MOL	23.78
Physical MOL MOD	23.78
Physical MOL MOD Material	23.78 1.1 Glass
Physical MOL MOD Material Lens Finish	23.78 1.1 Glass Gloss White
Physical MOL MOD Material Lens Finish Lens Material	23.78 1.1 Glass Gloss White Glass
Physical MOL MOD Material Lens Finish Lens Material Housing Color	23.78 1.1 Glass Gloss White Glass White
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.)	23.78 1.1 Glass Gloss White Glass White
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	23.78 1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info	23.78 1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Use	23.78 1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note	23.78 1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs -
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Use Specification Note Warranty	23.78 1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs -
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note Warranty Compliance	23.78 1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus - Classified; cRUus -
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note Warranty Compliance Safety Listing	23.78 1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus - Classified; cRUus - Recognized Component
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note Warranty Compliance Safety Listing Location Rating Energy Star	23.78 1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus - Classified; cRUus - Recognized Component Damp
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note Warranty Compliance Safety Listing Location Rating	23.78 1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus - Classified; cRUus - Recognized Component Damp No
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Specification Note Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	23.78 1.1 Glass Gloss White Glass White 0.24 Equivalent CCT selectable option available in S11764 Approved for use with tube guards Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus - Classified; cRUus - Recognized Component Damp No Yes

California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







