

# DOCK LIGHT DESCRIPTION






## SPECIAL OUTDOOR LIGHT

MODEL: DLL 320



| NOMENCLATURE | LUMENS(LM) | EFFICACY(LPW) | INPUT VOLTAGE | CRI | DISTRIBUTION | EQUIVALENCY(W) | OPERATING TEMP | WARRANTY |
|--------------|------------|---------------|---------------|-----|--------------|----------------|----------------|----------|
| DLL320-25W   | 2913LM     | UP TO 119LPW  | 120V          | >70 | 2HX2V        | 70W MH         | -30-40°C       | 5 YEARS  |



| MODEL  | WATTAGE | CCT                        | VOLTAGE        | DIMMING OPTION                 | MECHANICAL ACCESSORIES           | HOUSING FINISH  | MOUNTING                                  |
|--------|---------|----------------------------|----------------|--------------------------------|----------------------------------|---|---|
| DLL320 | 25W     | 40K = 4000K<br>50K = 5000K | V8 = 120V-277V | N = Non-Dimming<br>D = Dimming | WG = Wire Guard<br>ST = Standard | BZ = B ronze<br>WH = White<br>BK = Black<br>SL = Silver<br>GY = Gray<br>YE = Yellow | 60 = 60" Arm<br>42 = 42" Arm<br>NA = None |

ORDERING INFORMATION (DLL320-25W-40K-V8-D-ST-YE-42)

### PHOTOMETRY

DLL-320-23W-2HX2V  
Mounting Height=10.00 FT



SCALE: 1 INCH = 10 FT.  
LIGHT LOSS FACTOR = 1.00

MAXIMUM CALCULATED VALUE = 237.42 FC  
FOOT CANDLE = 5 10 20

- Impact & weather resistant fixture with die cast housings and tempered glass lenses
- individual optics for controlled beam
- optional wall mount arm with different lengths(42" and 60")
- High quality chip and driver @ 5 year warranty