



ProLume® Standard Metal Halide

Halco
LIGHTING TECHNOLOGIES®

ProLume® Standard Metal Halide lamps are unaffected by ambient temperature and are suitable for indoor and outdoor use. These lamps provide better light quality and are more efficient than High Pressure Sodium or Mercury Vapor.

Specifications:

- 175 to 1500 watts
- 3700K-4000K
- Clear and coated
- Up-to 20,000 hours average rated life
- Improved lumen maintenance
- High efficacy, up to 110 lumens per watt
- Improved color rendering compared to HPS

- » Shatter proof lamps are available in 175, 250 and 400 watts

Markets:

- Industrial
- Commercial

Applications:

- Municipal lighting
- Retail
- Security lighting
- Street lighting

where there's light, there's halco®

Contact your account representative at 800.677.3334 for pricing, orders and technical support.

Visit us at halcolighting.com

Ordering Information

Bulb Type	Base	Product #	Product Code	Description	Fixture Type	ANSI Ballast Type	Color Temp.	CRI	Initial Lumens	Avg. Rated Life	Pkg. Qty.	MOL
175 Watt												
ED28	Mog.	108200	MH175/U	Clear	E	M57/E	4000	65	15200	10000	1/12	8.25"
ED17	Med.	108262	MH175/U/MED	Clear	E	M57/E	4000	65	15000	10000	1/12	5.45"
ED28	Mog.	108202	MH175/C/U	Coated	E	M57/E	3700	70	14800	10000	1/12	8.25"
ED17	Med.	108264	MH175/C/U/MED	Coated	E	M57/E	3700	70	14800	10000	1/12	5.45"
250 Watt												
ED28	Mog.	108204	MH250/U	Clear	E	M58/E	4000	65	21000	10000	1/12	8.25"
ED28	Mog.	108604	MH250/U/CSTF	Clear PFA	E	M58/E	4000	65	21000	10000	1/12	8.25"
ED28	Mog.	60303	MH250/HOR	Clear	E	M58/E	4000	65	23000	10000	1/12	8.25"
T15	Mog.	108220	MH250/HBU/T15	Clear	E	M58/E	4000	65	21000	10000	1/12	8.30"
ED28	Mog.	108206	MH250/C/U	Coated	E	M58/E	3700	70	20000	10000	1/12	8.25"
ED28	Mog.	60302	MH250/C/HOR	Coated	E	M58/E	3700	70	22000	10000	1/12	8.25"
360 Watt												
ED37	Mog.	108212	MH360/BU/ES	Clear	E	M165/E M59/E	4300	65	36000	20000	1/6	11.50"
400 Watt												
ED37	Mog.	108208	MH400/U	Clear	E	M59/E	4000	65	36000	20000	1/6	11.50"
ED37	Mog.	108600	MH400/U/CSTF	Clear PFA	E	M59/E	4000	65	36000	20000	1/6	11.50"
ED28	Mog.	108216	MH400/U/ED28	Clear	E	M59/E	4000	65	36000	20000	1/12	8.25"
ED37	Mog.	61201	MH400/BU/LU	LU Retrofit	E	S51/E	4000	65	38000	10000	1/12	11.50"
ED18	Mog.	108218	MH400/HBU/ED18	Clear	E	M59/E	4000	65	36000	20000	1/12	9.75"
ED37	Mog.	60301	MH400/C/HOR	Coated	E	M59/E	3700	70	36800	20000	1/6	11.50"
ED28	Mog.	60201	MH400/C/U/ED28	Coated	E	M59/E	3700	70	34000	20000	1/12	8.25"
ED37	Mog.	108210	MH400/C/U	Coated	E	M59/E	3700	70	34000	20000	1/6	11.50"
BT56	Mog.	108222	MH1000/U	Clear	E	M47/E	4000	65	110000	12000	1/6	15.40"
BT37	Mog.	108226	MH1000/U/BT37	Clear	E	M47/E	4000	65	110000	12000	1/6	11.50"
BT56	Mog.	108214	MH1500/BU	Clear	E	M48/E	3400	65	161000	3000	1/6	15.40"

(Hg) Hg-LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.
 Visit www.lamprecycle.org for disposal information for your state or local government.

WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. This lamp complies with FDA radiation performance standard 21 CFR subchapter J.