Light Pole Accessories



Size: 4" $(4" \times 4")$, **5"** $(5" \times 5")$

SQUARE EXTERNAL MOUNT HORIZONTAL TENON · To mount 2/3/4 fixtures on an existing pole 20.5" (520 Low Profile Bullhorn with 3 Tenons Low Profile Bullhorn with 2 Tenons WSD-VTS4R-3T-D WSD-VTS4R-2T-D MAX EPA: 1.0 MAX FPA: 1.6 Finish: Dark Bronze Finish: Dark Bronze The Bracket is designed to mount over The Bracket is designed to mount over 2-3/8" O.D. vertical tenon. 24.6" (624.38m 2-3/8" O.D. vertical tenon. Triple 120° Horizontal Tenon Adapter Quad 90° Horizontal Tenon Adapter WSD-QT120-3T-D WSD-VTS4R-3T-D MAX EPA: 1.4 MAX EPA: 1.6 Finish: Dark Bronze Finish: Dark Bronze The Bracket is designed to mount over The Bracket is designed to mount over 2-3/8" O.D. vertical tenon. 2-3/8" O.D. vertical tenon. **WALL BRACKET** MID-POLE TENON BRACKET · Attaches to any flat surface · Provides wiring access 90° Wall Mount Bracket with 2-3/8" O.D. Tenon 2-3/8" OD Horizontal Tenon Mid-Pole Bracket Ø2.36 WSD-ADP2.5-90-D WSD-ADP2.5-D MAX EPA: 0.6 MAX EPA: 0.3 Finish: Dark Bronze Finish: Dark Bronze The 90° wall mount bracket with 2-3/8" 2-3/8" OD Horizontal Tenon Mid-Pole tenon attaches flood and area fixtures to Bracket is designed to mount light fixture almost any surface: wall, roof, or wood that is equipped with a adjustable slip-fitter onto a 2-3/8" OD horizontal tenon. pole. Provides wiring access and a built-in 2-3/8" O.D. tenon to mount a fixture with our adjustable slip-fitter. Suggested 3/8" diameter bolts for mounting. 180° Wall Mount Bracket with 2-3/8" O.D. Tenon 2-3/8" OD Horizontal Tenon Arc Adapter WSD-ADP2.5-180L3.9-D WSD-ADP2.5-BAR5-D MAX FPA: 0.5 MAX FPA: 0.3 Finish: Dark Bronze Finish: Dark Bronze The 180° wall mount bracket with 2-3/8" For use with Round, non-tapered steel and aluminum poles.2-3/8" OD Horizontal tenon attaches flood and area fixtures to almost any surface: wall, roof, or wood Tenon Mid-Pole Bracket is designed to pole. Provides wiring access and a built-in mount light fixture that is equipped with a 2-3/8" O.D. tenon to mount a fixture with adjustable slip-fitter onto a 2-3/8" OD our adjustable slip-fitter. Suggested 3/8" horizontal tenon. diameter bolts for mounting. **POLE BRACKET** • For mounting one fixture on an existing pole 4" Square Pole Mount with 2-3/8" O.D. Tenon 3" Round Pole Mount with 2-3/8" O.D. Tenon WSD-VTS4-D WSD-VT3-D MAX EPA: 0.3 MAX EPA: 0.3 Finish: Dark Bronze Finish: Dark Bronze For use with square, non-tapered steel and For use with round, non-tapered steel and 8.6" aluminum poles. Furnished with four 5/16" aluminum poles. Furnished with four 3/8" hex head stainless-steel bolts. Vertical hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D. and is made of tenon measures 2-3/8" O.D. 3.5" steel tubing. 5" Square Pole Mount with 2-3/8" O.D. Tenon 4" Round Pole Mount with 2-3/8" O.D. Tenon WSD-VTS5-D WSD-VT4-D MAX EPA: 0.3 MAX EPA: 0.3 Finish: Dark Bronze Finish: Dark Bronze For use with round, non-tapered steel and For use with square, non-tapered steel and 8.6 aluminum poles. Furnished with four 5/16" aluminum poles. Furnished with four 3/8" hex head stainless-steel bolts. Vertical hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of tenon measures 2-3/8" O.D. steel tubing. 1/2" Round Pole Mount with 2-3/8" O.D. Tenon 5" Round Pole Mount with 2-3/8" O.D. Tenon Ø2.13 WSD-VT5-D WSD-TADP2.5-1/2-D MAX EPA: 0.3 MAX EPA: 0.3 Finish: Dark Bronze Finish: Dark Bronze For use with Round, non-tapered steel and For use with round, non-tapered steel and aluminum poles. Furnished with four 3/8" aluminum poles. Vertical tenon measures hex head stainless-steel bolts. Vertical ten-2-3/8" O.D., and is made of aluminum on measures 2-3/8" O.D., and is made of tubing. steel tubina.

Light Pole Accessories



Size: 4" (4" × 4"), **5"** (5" × 5")

ROUND EXTERNAL MOUNT HORIZONTAL TENON · To mount 2/3/4 fixtures on an existing pole Double 90° Horizontal Tenon Adapter Triple 120° Horizontal Tenon Adapter WSD-SB2.5TW90-D WSD-SB2.5TR120-D 10.23" MAX EPA: 0.6 MAX EPA: 0.7 Finish: Dark Bronze Finish: Dark Bronze The Bracket is designed to mount over The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Two 2-3/8" (60mm) O.D. vertical tenon. Three fixtures can be mounted to the Round fixtures can be mounted to the Round External Mount Horizontal Tenon and ø2.667 External Mount Horizontal Tenon and adjusted horizontally. adjusted horizontally. Double 180° Horizontal Tenon Adapter Quad 90° Horizontal Tenon Adapter WSD-SB2.5TW180-D WSD-SB2.5QD90-D MAX EPA: 0.4 MAX EPA: 0.3 Finish: Dark Bronze Finish: Dark Bronze The Bracket is designed to mount over The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Two 2-3/8" (60mm) O.D. vertical tenon. Four Ø2.36 fixtures can be mounted to the Round fixtures can be mounted to the Round External Mount Horizontal Tenon and External Mount Horizontal Tenon and adjusted horizontally. adjusted horizontally. Single Spoke Bracket Tenon Adapter Double 180° Horizontal Tenon Adapter WSD-SB2.5S90-D WSD-RB2.5D180-D 10.23" 10.23" MAX EPA: 0.4 MAX EPA: 0.9 Finish: Dark Bronze Finish: Dark Bronze The Bracket is designed to mount over The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. One 2-3/8" (60mm) O.D. vertical tenon. Two fixtures can be mounted to the Bound fixtures can be mounted to the Round External Mount Horizontal Tenon and External Mount Horizontal Tenon and ø2.677 adjusted horizontally. adjusted horizontally. Triple 180° Horizontal Tenon Adapter Quad 90° Horizontal Tenon Adapter WSD-RB2.5TR180-D WSD-RB2.5QD90-D MAX EPA: 1.5 MAX EPA: 1.4 02.36 Finish: Dark Bronze Finish: Dark Bronze The Bracket is designed to mount over The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Three 2-3/8" (60mm) O.D. vertical tenon. Four fixtures can be mounted to the Round fixtures can be mounted to the Round External Mount Horizontal Tenon and External Mount Horizontal Tenon and adjusted horizontally. adjusted horizontally. 90° Wall Mount Bracket with 2-3/8" O.D. Tenon Double 180° Horizontal Tenon Adapter WSD-ADP2.5-90H-D WSD-RB2.5TR180H-D MAX EPA: 0.7 MAX EPA: 1.0 Finish: Dark Bronze Finish: Dark Bronze The 90° wall mount bracket with 2-3/8" The Bracket is designed to mount over tenon attaches flood and area fixtures to 2-3/8" (60mm) O.D. vertical tenon. Two almost any surface; wall, roof, or wood fixtures can be mounted to the Round pole. Provides wiring access and abuilt-in External Mount Horizontal Tenon and 2-3/8" O.D. tenon to mount a fixture with adjusted horizontally. our adjustable slip-fitter. Suggested 3/8" diameter bolts for mounting. Mounting holes are spaced 3-1/4" apart. Double 180° Wall Mount Bracket with 2-3/8" Triple 120° Horizontal Tenon Adapter WSD-SB2.5TR120V-D O.D. Tenon WSD-ADP2.5-180H-D MAX FPA: 1.5 MAX EPA: 1.4 Finish: Dark Bronze Finish: Dark Bronze The Bracket is designed to mount over The 180° wall mount bracket with 2-3/8" 2-3/8" (60mm) O.D. vertical tenon. Three tenon attaches flood and area fixtures to fixtures can be mounted to the Round almost any surface: wall, roof, or wood External Mount Horizontal Tenon and pole. Provides wiring access and abuilt-in adjusted horizontally. 2-3/8" O.D. tenon to mount a fixture with our adjustable slip-fitter. Suggested 3/8" diameter bolts for mounting. Mounting holes are spaced 3-1/4" apart.

Light Pole Accessories



Size: 4" (4" × 4"), **5"** (5" × 5")

MOUNTING OPTIONS: WSD-NEWSBARM2-D WSD-NEWSBSF2-D Finish: Dark Bronze Finish: Dark Bronze Arm Mount 4" and 5" Square and Round Slipfitter Mount An optional cast aluminum poles. Standard versatile mounting arm mast arm adapter secures fixture head to is simple to install and can be used with nominal 2"(2-3/8"O.D. pipe size) horizontal existing poles for retro installations. steel tenon arm. WSD-SBT-D WSD-SFARM2-D Finish: Dark Bronze Finish: Dark Bronze Easy to install for direct wall mounting with SFARM2 Mount An optional cast aluminum 1/2" conduit wiring. mast arm adapter secures fixture head to nominal 2"(2-3/8"O.D. pipe size) horizontal steel tenon arm. 0.31" (8mm) **Anchor Bolt** Anchor Bolt Positioning Plate WSD-BMS-S WSD-SPP-D Finish: Silver Finish: Dark Bronze Before installing the lamp pole, the instal-This is a screw rod positioning plate. After the screw rod of the lamp rod base is fixed lation hook should be buried underground and fixed by cement After fixing, the lamp underground, the positioning plate is fixed pole should be fixed by locking screw and with the screw rod to prevent the screw base installed. rod from deviation. Finally, the lamp rod is locked. **Install Base Shield Install Base Shield** WSD-IBS4-D WSD-IBS5-D Finish: Dark Bronze Finish: Dark Bronze The 5" Installation of base shield is used The 4" Installation of base shield is used to protect the base after fixing the lamp to protect the base after fixing the lamp pole, so that the lamp pole base is not pole, so that the lamp pole base is not damaged, thereby increasing the service damaged, thereby increasing the service life of the lamp pole. life of the lamp pole. **Arm Square Tube Turn Tube Tenon Adapter** Arm Square Tube Turn Tube Tenon Adapter WSD-SADP-BAR-D WSD-ARM-BAR-D Finish: Dark Bronze Finish: Dark Bronze Round tube light bar installation, with Arm Round tube light bar installation, with Arm installation of lamps. installation of lamps. Ø0.7" Ø0.35 0.78"

