

# MicroMAX CFL Spirals



## MINI CFL SPIRALS

Ideal for table and floor lamps, recessed lighting fixtures, wall sconces and other corridor lighting fixtures in homes, offices, restaurants, schools, hospitals, and retail and hospitality applications, the compact fluorescent lamp (CFL) MicroMax is available in 2700K (warm white), 4100K (cool white) and 5000K (daylight) correlated color temperatures (CCT) and has a long life of up to 10,000 hours. ENERGY STAR®-rated models are available.

PROJECT NAME
CATALOG NUMBER
NOTES
FIXTURE TYPE

## FEATURES:

- Ultra mini size fits most fixtures
- Long life – lasts up to 10,000 hours
- Saves up to 75% in energy costs
- Instant-on, flicker-free electronics
- Available in Warm White, Cool White and Daylight
- E26 Base

## Specification:

- Ballast Type: Electronic
- Starting Method: Instant Start
- Input Line Voltage: 120VAC
- Input Line Frequency: 60Hz
- Mini. Starting Temp.: 0°F
- Max. Operating Temp.: 100°F
- Color Rendering Index: ≥ 82



### Luminaire Ordering Information:

Watts	Order Number	Model Number	Incandescent Equivalent	Delivered Lumens	Pack Type (Case Pack)	Life (Hrs.)	Dimensions (W"xH")	CCT
* 20	01427	MLM20SCW	75	1200	Box (48)	10,000	2.40 x 4.90	4100
* 20	11129	MLM20SDL	75	1200	Box (48)	10,000	2.40 x 4.90	5000
* 20	72614	SKS20WW-180	75	1200	Box (48)	8,000	2.32 x 4.75	2700
* 20	72615	SKS20CW-180	75	1100	Box (48)	8,000	2.32 x 4.75	4100
25	70865	MLS25EACW	100	1600	Box (48)	10,000	2.4 x 5.4	4100
* 27	72616	SKS27WW-180	100	1610	Box (48)	8,000	2.32 x 5.25	2700
* 27	72617	SKS27CW-180	100	1530	Box (48)	8,000	2.32 x 5.25	4100
* 30	72264	MLM30SWW-110	125	2000	Box (48)	10,000	2.7 x 5.7	2700
30	01465	MLM30SCW	125	2000	Box (48)	10,000	2.7 x 5.7	4100
30	11152	MLM30SDL	125	2000	Box (48)	10,000	2.7 x 5.7	5000
* 42	41023	MLM42SWW	150	2800	Box (24)	10,000	2.8 x 7.2	2700
42	41021	MLM42SCW	150	2600	Box (24)	10,000	2.8 x 7.2	4100
42	41026	MLM42SDL	150	2600	Box (24)	10,000	2.8 x 7.2	5000

\* Energy Star Qualified

MAX12138