

PROJECT		
TYPE		

# **OUTDOOR WALL/CEILING FIXTURE S791WF OUTDOOR DECORATIVE MARLEX**

VOLTAGE



**SPECIFICATIONS** 

• Wall or Ceiling Mount

• Mounting Hardware Included

• Frosted Polycarbonate Diffuser

• Minimum Starting Temp -20°F

• UL Listed for Wet Locations


Composite Construction

WH WHITE

· Black or White

Non-Corrosive

**BK** BLACK



Wave Lighting's S791WF adds a contemporary look to any outdoor space. Wave Lighting's S791WF is designed for wall or ceiling applications and mounting hardware is included. Options include photocell.













## LED SOURCE OPTIONS

### LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L<sub>70</sub>
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty
- Energy Star

#### LED MULTI-VOLT SYSTEM - L22

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs  $L_{70}$
- 4000K CCT 80 CRI
- 3 Year WarrantY

#### **E26 MEDIUM BASE - LE26**

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs  $L_{70}$
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty
- Energy Star

## **GUIDE CODE: S791WF-LR12W-WH-PC**

#### **CALL FOR PHOTOMETRIC INFORMATION**

ITEM#	DIFFUSER	LIGHT SOURCE	ССТ	COLOR	OPTIONS
F-Frosted Ribbon	POLYCARBONATE	E26 MEDIUM BASE	<b>C</b> -4K	<b>BK</b> -Black	PC-Photocell
	POLYCARBONATE BACK PAN (1) 60W MAX Medium Base LE26-9.5W 800lm (E26 LED Lamp) + *	<b>W</b> -3K	WH-White	(120V Lightwave LED only)	
	120V LIGHTWAVE LED				
	ALUMINUM BACK PAN LR12-13W 1000lm 80CRI *				
	LR15-15W 1400Im 80CRI ★				
		LR22-23W 1900lm 80CRI ★ LT12-12W 1040lm 90CRI			
	<b>LT15</b> -16W 1400lm 90CRI <b>LT22</b> -24W 2020lm 90CRI				
		120-277V MULTI-VOLT LED			
		<b>L22</b> -22W 1824lm	4K		

**<sup>+</sup>** Lamp included. **★**Energy Star qualified product.