

TCP Standard LED Lamps, LED Filament Lamps and TCP Downlights have been tested to work with the following dimmers:

| BRAND | MODEL |
|---------|------------------|
| LUTRON | AYCL-153P |
| | CTCL-153PD-H |
| | CTCL-53PD-H |
| | DV-600P |
| | DV-600PR-WH |
| | DV-603PH-WH |
| | DVCL-153P |
| | LGCL-153P |
| | MACL_153M |
| | MSCL-OP153M |
| | PD-6WCL |
| | SCL-153PR |
| | SELV-300P |
| | TGCL-153P |
| | MRF2S-6ELV120-WH |
| LEVITON | 6811 |
| | 6602 |
| | 6631 |
| | 6672 |
| | 6672-L |
| | 6674 |
| | DSL06 |
| | IPL06 |
| | COOPER |
| SAL06P | |

*Dimming compatibility tests are performed under a controlled lab environment. Field conditions may vary from this type of environment. Dimmers may differ by age and versions under the same item number which may affect compatibility. Compatibility may also extend beyond this list as TCP products should work with most C-L Type Triac Dimmers. TCP recommends trying a few dimmer-lamp combinations in an on-site test to ensure compatibility and performance before a major installation. If there's a dimmer not on this list we can perform a lab test for compatibility.

LED Recessed Flat Face Snap-In CCT Selectable Downlights

Product Specifications



TCP's LED Recessed Flat Face Snap-In CCT Selectable Downlights are the perfect choice for remodeling or new construction projects. The slim, energy-efficient design is easy to install and offers a rated lifetime of 50,000 hours.

Reasons to choose the LED Recessed Flat Face Snap-In CCT Selectable Downlights from TCP

- 4", 6", and 8" diameter sizes
- Direct wire - no recessed can required
- Integrated junction box on 4" and 6" models
- Easy installation
- Dimmable
- Slim, low-profile design
- Excellent color consistency
- Selectable CCT (27K/30K/35K) or (30K/40K/50K)
- 50,000 hour rated life
- UL approved for damp locations
- IC rated
- Back-lit technology

Ideal Applications

- Retrofits
- New construction
- Residential
- Office
- Retail
- Hospitality
- Drop ceilings
- Remodeling

Applications

Ideal for dimmable 4", 6" and 8" retrofit or new construction downlight applications.

Construction

- Integrated junction box for direct wire application (4" and 6" models)
- 8" models have external junction box
- Spring loaded tabs for easy installation

Electrical

- UL approved for damp locations
- Easily access wiring for quick installation
- 50,000 hour rated life

Optics

- Excellent color consistency
- Smooth, uniform dimming (only with 120V application)
- Highly efficient LEDs and driver
- Triac dimming

Accessories

- 4"/6" Adjustable Frame Kit is also available: 46INFRAMEKIT



Listings

cULus Listed, RoHS

Warranty

Five year limited warranty against defects in manufacturing.

LED Recessed Flat Face Snap-In CCT Selectable Downlights

| ITEM # | DESCRIPTION | VOLTAGE | INCAND. WATTS | WATTAGE | LUMENS | LPW | CCT SELECTABLE | BEAM ANGLE | MOL (IN) | DIAMETER (IN) |
|-----------|-------------------------|---------|---------------|---------|--------|------|----------------|------------|----------|---------------|
| DR4BLCCT1 | 4" SNAP-IN CCT 27/30/35 | 120 | 75 | 10 | 850 | 85 | 27K/30K/35K | 90° | 3 | 5 |
| DR4BLCCT2 | 4" SNAP-IN CCT 30/40/50 | 120 | 75 | 10 | 850 | 85 | 30K/40K/50K | 90° | 3 | 5 |
| DR6BLCCT1 | 6" SNAP-IN CCT 27/30/35 | 120 | 85 | 14 | 1100 | 78.6 | 27K/30K/35K | 100° | 3 | 7.125 |
| DR6BLCCT2 | 6" SNAP-IN CCT 30/40/50 | 120 | 85 | 14 | 1100 | 78.6 | 30K/40K/50K | 100° | 3 | 7.125 |
| DR8BLCCT1 | 8" SNAP-IN CCT 27/30/35 | 120 | 120 | 22 | 1800 | 81.8 | 27K/30K/35K | 110° | 1.5 | 8.75 |
| DR8BLCCT2 | 8" SNAP-IN CCT 30/40/50 | 120 | 120 | 22 | 1800 | 81.8 | 30K/40K/50K | 110° | 1.5 | 8.75 |